

BNC Female Bulkhead to BNC Female Bulkhead
Cable Using RG174 Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet



PE3202/HS

Configuration

- Connector 1: BNC Female Bulkhead
- Connector 2: BNC Female Bulkhead
- Cable Type: RG174

Features

- Max Frequency 1 GHz
- 66% Phase Velocity
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3202/HS BNC female bulkhead to BNC female bulkhead cable using RG174 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to BNC cable assembly has a female to female gender configuration with 50 ohm flexible RG174 coax. The PE3202/HS BNC female to BNC female cable assembly operates to 1 GHz. Our RF cable assembly with BNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink PE3202/HS](#)

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet

PE3202/HS

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1,000	MHz
VSWR			1.4:1	
Velocity of Propagation		66		%
Capacitance		31.08 [101.97]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	100	250	400	500	1,000	MHz
Insertion Loss (Typ.)	0.084	0.137	0.19	0.211	0.32	dB/ft
	0.28	0.45	0.62	0.69	1.05	dB/m

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.1 dB for the straight connector.

Mechanical Specifications

Cable Assembly

Weight 0.098 lbs [44.45 g]

Cable

Cable Type	RG174
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel
Dielectric Type	PE
Number of Shields	1
Shield Layer 1	Tinned Copper Braid
Jacket Material	PVC, Black
Jacket Diameter	0.11 in [2.79 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink PE3202/HS](#)

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet

PE3202/HS

Connectors

Description	Connector 1	Connector 2
Type	BNC Female Bulkhead	BNC Female Bulkhead
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 μ in minimum	30 μ in minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 μ in minimum	100 μ in minimum

Environmental Specifications

Temperature

Operating Range

-40 to +80 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink PE3202/HS](#)

BNC Female Bulkhead to BNC Female Bulkhead
Cable Using RG174 Coax with HeatShrink




RF Cable Assemblies Technical Data Sheet

PE3202/HS

How to Order

Part Number Configuration:



Example: PE3202/HS-12 = 12 inches long cable
PE3202/HS-100cm = 100 cm long cable

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink PE3202/HS](#)


URL: <https://www.pasternack.com/bnc-female-bulkhead-to-bnc-female-bulkhead-cable-using-rg174-with-heatshrink-pe3202-hs-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3202/HS CAD Drawing

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink

ZONE	REV.	DESCRIPTION	DATE	CHANGED BY	APPROVED BY
	A	INITIAL RELEASE	12/14/2022		AGANIWANI



NOTES:

1. CABLE ASSEMBLY LENGTH LABEL PLACEMENT: 36 INCHES OR LESS , ONE LABEL APPROXIMATELY CENTERED, LONGER THAN 36 INCHES, TWO LABELS APPROXIMATELY 6 INCHES FROM EACH CONNECTOR.
2. CABLE ASSEMBLIES SHALL BE TESTED FOR CONTINUITY

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED.

				<p>INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5</p> <p>SCALE SHEET</p> <p>NONE 1 OF 1</p>		REV A								
<p>OTHERWISE SPECIFIED DIMENSIONS ARE INCHES UNLESS OTHERWISE SPECIFIED IN MILLIMETERS</p> <p>TOLERANCES:</p>		<p>FRACTIONS</p> <table border="1"> <tr> <td>[5]</td><td>± 1/32</td></tr> <tr> <td>[5]</td><td>± 1/16</td></tr> <tr> <td>05</td><td>± 1/32</td></tr> <tr> <td>13</td><td>± 1/16</td></tr> </table> <p>ANGLES ± 1°</p>		[5]	± 1/32	[5]	± 1/16	05	± 1/32	13	± 1/16	<p>WEBSITE: www.Pasternack.com</p> <p>PHONE: 1.866.727.8376 1.949.261.1920</p>		
[5]	± 1/32													
[5]	± 1/16													
05	± 1/32													
13	± 1/16													
<p>LENGTH TOLERANCES:</p>		<p>DESCRIPTION</p> <p>BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG174 Coax with HeatShrink</p>		<p>ITEM NO.</p> <p>PE3202/HS</p>										
<p>1.000 [25.4]</p> <p>± 0.000 [0]</p>		<p>SIZE</p> <p>A</p>		<p>DRAWN BY</p> <p>BPUCHASKI</p>										
<p>3.000 [76.200]</p> <p>± 0.000 [0]</p>		<p>CAGE CODE</p> <p>53919</p>		<p>REFERENCE ONLY IT IS THE DUTY OF THE PURCHASER TO CHANGE THIS DRAWING IF IT IS OUT OF DATE.</p>										