



SMA Male to SMA Male Right Angle Low Loss Cable  
72 Inch Length Using PE-P141 Coax, RoHS

TECHNICAL DATA SHEET

PE351-72

**Configuration**

Connector 1	SMA Male
Connector 2	SMA Male Right Angle
Cable Type	PE-P141

**Electrical Specifications**

Frequency Range	DC to 18 GHz
Impedance	50 Ohms
Maximum VSWR	1.4:1
Maximum Insertion Loss	1 dB
Velocity of Propagation	70 %
RF Shielding	110 dB

**Typical Performance by Frequency**

**Frequency 1**

Frequency	6 GHz
VSWR	1.15:1
Insertion Loss,	2.4 dB

**Frequency 2**

Frequency	12 GHz
VSWR	1.3:1
Insertion Loss	3.6 dB

**Frequency 3**

Frequency	18 GHz
VSWR	1.4:1
Insertion Loss	4.5 dB

**Mechanical Specifications**

**Temperature**

Temperature Operating Range	-55 to +200 deg C
-----------------------------	-------------------

**Size**

Length	72 in [182.88 cm]
Diameter	0.74 in [18.8 mm]
Cable Color	Blue
One Time Minimum Bend Radius	0.8 in [20.32 mm]

**Cable**

Cable Type	PE-P141
Inner Conductor Type	Solid
Cable Inner Conductor	Copper Clad Steel, Silver
No of Shields	2
Cable Outer Conductor	Copper, Silver
Dielectric Type	PTFE

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Right Angle Low Loss Cable 72 Inch Length Using PE-P141 Coax, RoHS PE351-72](#)



## SMA Male to SMA Male Right Angle Low Loss Cable 72 Inch Length Using PE-P141 Coax, RoHS

### TECHNICAL DATA SHEET

PE351-72

Jacket Material	FEP
Jacket Diameter	0.163 in [4.14 mm]
<b>Connector 1</b>	
Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Beryllium Copper, Gold
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size	5/16 inch
Torque	8 in-lbs [0.9 Nm]
Body Material and Plating	Passivated Stainless Steel
Dielectric Type	PTFE
<b>Connector 2</b>	
Type	SMA Male Right Angle
Configuration	Right Angle
Inner Conductor Material and Plating	Beryllium Copper, Gold
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size	5/16 inch
Torque	8 in-lbs [0.9 Nm]
Body Material and Plating	Passivated Stainless Steel
Dielectric Type	PTFE

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant	Yes
Notes:	
• Values at +25 °C, sea level	

SMA Male to SMA Male Right Angle Low Loss Cable 72 Inch Length Using PE-P141 Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Right Angle Low Loss Cable 72 Inch Length Using PE-P141 Coax, RoHS PE351-72](http://www.pasternack.com/sma-male-sma-male-pe-p141-cable-assembly-pe351-72-p.aspx)


URL: <http://www.pasternack.com/sma-male-sma-male-pe-p141-cable-assembly-pe351-72-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE351-72 CAD Drawing

SMA Male to SMA Male Right Angle Low Loss Cable

72 Inch Length Using PE-P141 Coax, RoHS



How To Order		Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
Part Number Configuration		-12	12"	-25CM	25Cm
PE3	zzz yv - xx uu	-24	24"	-50CM	50Cm
00 - 99999	LF = RoHS Compliant < Blank > = Standard	-36	36"	-75CM	75Cm
	Note: LF applies only to RF cables	-48	48"	-100CM	100Cm
		-60	60"	-125CM	125Cm
		-xx	Custom Length	-xxCM	Custom Length

NOTES:  
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
 3. DIMENSIONS ARE IN INCHES [mm].  
 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.

DWG TITLE  
**PE351**

**PE PASTERNAK**  
 THE ENGINEER'S RF SOURCE  
 Pasternack Enterprises, Inc.  
 P.O. Box 16759 | Irvine | CA | 92623  
 Phone: (949) 261-1920 | Fax: (949) 261-7451  
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAD FILE	041814	SCALE	N/A	SIZE	A
FSCM NO.	53919				2233