

## MCX Plug to Straight Cut Lead Cable Using RG316 Coax

### PE36087




#### Configuration

- Connector 1: MCX Plug
- Connector 2: Straight Cut Lead
- Cable Type: RG316
- Coax Flex Type: Flexible

#### Features

- FEP Jacket



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE36087 50 ohm MCX plug to straight cut lead cable using RG316 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Capacitance		32 [104.99]		pF/ft [pF/m]

#### Mechanical Specifications

##### Cable Assembly

Weight 0.019 lbs [8.62 g]

##### Cable

Cable Type	RG316
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	1
Shield Layer 1	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.098 in [2.49 mm]

MCX Plug to Straight Cut Lead Cable Using RG316 Coax



PE36087

Connectors

Description	Connector 1	Connector 2
Type	MCX Plug	Straight Cut Lead
Specification	CECC 22220	
Impedance	50 Ohms	0 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	
Contact Plating Specification	30 µin minimum	
Dielectric Type	PTFE	
Body Material and Plating	Brass, Nickel	
Body Plating Specification	100 µin minimum	

Environmental Specifications

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:  
Values at 25°C, sea level.

## MCX Plug to Straight Cut Lead Cable Using RG316 Coax



### PE36087

#### Typical Performance Data

#### How to Order

Part Number Configuration:

**PE36087**

**- xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches

Length

Base Number

Example: PE36087-12 = 12 inches long cable  
PE36087-100cm = 100 cm long cable

MCX Plug to Straight Cut Lead Cable Using RG316 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug to Straight Cut Lead Cable Using RG316 Coax PE36087](#)

URL: <https://www.pasternack.com/mcx-plug-to-straight-cut-lead-cable-using-rg316-pe36087-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE36087 CAD Drawing
MCX Plug to Straight Cut Lead Cable Using RG316 Coax

