



7/16 DIN Male to 7/16 DIN Male Cable Using 1/2 inch Helical Coax, RoHS

TECHNICAL DATA SHEET

PE37971

7/16 DIN Male to 7/16 DIN Male Cable Using 1/2 inch Helical Coax, RoHS

Configuration

Connector 1 7/16 DIN Male
Connector 2 7/16 DIN Male
Cable Type 1/2" Helical

Electrical Specifications

Frequency Range, GHz
Impedance, Ohms
50
Maximum VSWR
1.12:1
Passive Intermodulation, dBc
-156

Typical Performance by Frequency

Frequency 1

 Frequency, MHz
 1000

 VSWR
 1.05:1

 Insertion Loss
 0.022 dB/ft + 0.02 dB [0.07 dB/m + 0.02 dB]

Frequency 2

Frequency, GHz 2.2 VSWR 1.07:1

Insertion Loss 0.034 dB/ft + 0.02 [0.11 dB/m + 0.02 dB]

Frequency 3

Frequency, GHz 2.7 VSWR 1.08:1

Insertion Loss 0.038 dB/ft + 0.02 dB [0.12 dB/m + 0.02 dB]

Mechanical Specifications

Cable Assembly

Cable Type 1/2" Helical

Temperature

Temperature Operating Range, deg C -55 to +85

One Time Minimum Bend Radius, in [mm] 2.75 [69.85]

Repeated Minimum Bend Radius, in [mm] 4.9 [124.46]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 7/16 DIN Male to 7/16 DIN Male Cable Using 1/2 inch Helical Coax, RoHS PE37971

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.





7/16 DIN Male to 7/16 DIN Male Cable Using 1/2 inch Helical Coax, RoHS

TECHNICAL DATA SHEET

PE37971

Cable

Center Conductor Type Solid

Cable Inner Conductor Copper Clad Aluminum

No of Shields

Dielectric Type PE (F)
Jacket Material PE

Jacket Diameter, in [mm] 0.54 [13.72]

Connector 1

Type 7/16 DIN Male Configuration Straight

Inner Conductor Material and Plating
Outer Conductor Material and Plating
Coupling Nut Material and Plating
Brass, Silver
Body Material and Plating
Brass, Silver
Brass, Silver
Brass, Silver

Dielectric Type PTFE

Connector 2

Type 7/16 DIN Male
Configuration Straight
Inner Conductor Material and Plating Brass, Silver
Outer Conductor Material and Plating Brass, Silver

Coupling Nut Material and Plating Brass, Nickel Body Material and Plating Brass, Silver

Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

7/16 DIN Male to 7/16 DIN Male Cable Using 1/2 inch Helical Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 7/16 DIN Male to 7/16 DIN Male Cable Using 1/2 inch Helical Coax, RoHS PE37971

URL: http://www.pasternack.com/7-16-male-7-16-male-1-2-inch-helical-cable-pe37971-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

