

## Waterproof IP68 SMA Male (Plug) to N Female (Jack) Bulkhead Low Loss Cable Using LMR-240 Coax with Times Microwave Components




### PE3C1779/WP

#### Configuration

- Connector 1: SMA Male
- Connector 2: N Female Bulkhead
- Cable Type: LMR-240
- Coax Flex Type: Flexible

#### Features

- Max Frequency 6 GHz
- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- PE Jacket
- Silicone Connector Boot
- IP68 Rated



#### Applications

- General Purpose
- Laboratory Use

#### Description

The Pasternack PE3C1779/WP is a weatherproof low loss cable assembly that comes with SMA male connection with weatherproof boot on one end and type N female on the other. Pasternack's RF coaxial cable assembly products are designed for typical use, production, laboratory test and measurement, defense/military, aerial antenna towers, etc. The low loss cable has a 50 Ohm impedance and is specifically ready for quicker shipment than most in the industry can provide.

This weatherproof low loss RF cable assembly operates at a maximum frequency of 6 GHz. Our RF cable assembly has a PE jacket with 0.240 inches diameter. The SMA male to type N female cable assembly PE3C1779/WP is built with LMR-240 coax, which has a flexible design. This RF cable assembly with 0.5 inches diameter has copper as cable's inner conducting material and PE (F) dielectric type. The weatherproof boot low loss cable is reusable and can withstand elements including extreme temperature. Additional dimensions, specifications, and CAD drawings for this PE3C1779/WP low loss RF cable are available on our downloadable PDF datasheet.

Pasternack stocks a wide selection of weatherproof low loss cable assemblies that ship the same business day as ordered from our warehouse. Make your online purchase right now to take advantage of our same-day shipping. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the ideal SMA male to type N female cable assembly as per your requirements.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.4:1	
Velocity of Propagation		84		%
RF Shielding	90			dB
Capacitance		24.2 [79.4]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]

Waterproof IP68 SMA Male (Plug) to N Female (Jack)  
 Bulkhead Low Loss Cable Using LMR-240 Coax  
 with Times Microwave Components



## PE3C1779/WP

### Electrical Specifications

Description	Minimum	Typical				Maximum	Units
DC Resistance Inner Conductor	3.2 [10.5]				Ohms/1000ft [Ohms/Km]		
DC Resistance Outer Conductor	3.89 [12.76]				Ohms/1000ft [Ohms/Km]		
Dielectric Withstanding Voltage (DC)					1,500	Vdc	
Jacket Spark					5,000	Vrms	

### Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	250	500	1000	2500	6000	MHz	
PE3C1779/WP	Custom Lengths Available	Insertion Loss (Typ.)	0.039	0.055	0.079	0.129	0.204	dB/ft	
			0.13	0.19	0.26	0.43	0.67	dB/m	
PE3C1779/WP-24	24 Inch	Insertion Loss (Typ.)	0.28	0.31	0.36	0.46	0.61	dB	0.679
PE3C1779/WP-36	36 Inch	Insertion Loss (Typ.)	0.32	0.37	0.44	0.59	0.82	dB	0.712
PE3C1779/WP-48	48 Inch	Insertion Loss (Typ.)	0.36	0.42	0.52	0.72	1.02	dB	0.745
PE3C1779/WP-60	60 Inch	Insertion Loss (Typ.)	0.4	0.48	0.6	0.85	1.22	dB	0.778

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1 dB  
 Loss due to Connector 2: 0.1 dB  
 Base Weight: 0.646 pounds  
 Additional Weight per Inch: 0.00275 pounds

### Mechanical Specifications

#### Cable Assembly

Width/Diameter 0.5 in [12.7 mm]  
 Weight 0.646 lbs [293.02 g]

#### Cable

Cable Type LMR-240  
 Impedance 50 Ohms  
 Inner Conductor Type Solid  
 Inner Conductor Material and Plating Copper  
 Dielectric Type PE (F)  
 Number of Shields 2  
 Shield Layer 1 Aluminum Tape  
 Shield Layer 2 Tinned Copper Braid  
 Jacket Material PE  
 Jacket Diameter 0.24 in [6.1 mm]  
 One Time Minimum Bend Radius 0.75 in [19.05 mm]  
 Repeated Minimum Bend Radius 2.5 in [63.5 mm]  
 Bending Moment 0.25 lbs-ft [0.34 N-m]  
 Flat Plate Crush 20 lbs/in [0.36 Kg/mm]

Waterproof IP68 SMA Male (Plug) to N Female (Jack)  
 Bulkhead Low Loss Cable Using LMR-240 Coax  
 with Times Microwave Components



## PE3C1779/WP

Tensile Strength

80 lbs [36.29 Kg]

### Connectors

Description	Connector 1	Connector 2
Type	SMA Male	N Female Bulkhead
Option	Weatherproof Boot	
Specification	MIL-STD-348	MIL-STD-348
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Contact Plating Specification	ASTM B488	50 $\mu$ in minimum
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating	Passivated Stainless Steel, Gold	Brass, Tri-Metal
Outer Conductor Plating Specification		80 $\mu$ in minimum
Body Material and Plating	Passivated Stainless Steel, Gold	Brass, Tri-Metal
Body Plating Specification	SAE-AMS-2700	
Coupling Nut Material and Plating	Passivated Stainless Steel	
Coupling Nut Plating Specification	SAE-AMS-2700	
Boot Material	Silicone	

### Environmental Specifications

Ingress Protection (IP) Rating

IP68

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

Values at 25°C, sea level.

Waterproof IP68 SMA Male (Plug) to N Female (Jack)  
Bulkhead Low Loss Cable Using LMR-240 Coax  
with Times Microwave Components




## PE3C1779/WP

### Typical Performance Data

### How to Order

Part Number Configuration:



Example: PE3C1779/WP-12 = 12 inches long cable  
PE3C1779/WP-100cm = 100 cm long cable

Waterproof IP68 SMA Male (Plug) to N Female (Jack) Bulkhead Low Loss Cable Using LMR-240 Coax with Times Microwave Components from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Waterproof IP68 SMA Male \(Plug\) to N Female \(Jack\) Bulkhead Low Loss Cable Using LMR-240 Coax with Times Microwave Components PE3C1779/WP](#)

URL: <https://www.pasternack.com/waterproof-ip68-sma-male-plug-to-n-female-jack-bulkhead-low-loss-cable-using-lmr-240-pe3c1779-wp-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

# PE3C1779/WP CAD Drawing

Waterproof IP68 SMA Male (Plug) to N Female (Jack) Bulkhead Low Loss Cable Using LMR-240 Coax with Times Microwave Components

