



MMCX Plug to SMA Male Right Angle Cable 100 cm
Length Using LMR-100 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet


PE3C1997LF-100CM

Configuration

- Connector 1: MMCX Plug
- Connector 2: SMA Male Right Angle
- Cable Type: LMR-100A

Features

- Max Frequency 3 GHz
- Shielding Effectivity > 90 dB
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C1997LF-100CM MMCX plug to SMA male right angle 100 cm cable using LMR-100 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack MMCX to SMA cable assembly has a plug to male gender configuration with 50 ohm flexible LMR-100A coax. The PE3C1997LF-100CM MMCX plug to SMA male cable assembly operates to 3 GHz. The right angle SMA interface on the LMR-100A cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder PE3C1997LF-100CM](#)



MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3C1997LF-100CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.45:1	
Velocity of Propagation		66		%
RF Shielding	90			dB
Group Delay		1.54 [5.05]		ns/ft [ns/m]
Capacitance		30.8 [101.05]		pF/ft [pF/m]
Inductance		0.077 [0.25]		uH/ft [uH/m]
DC Resistance Inner Conductor		81 [265.75]		Ω/1000ft [Ω/Km]
DC Resistance Outer Conductor		9.5 [31.17]		Ω/1000ft [Ω/Km]
Jacket Spark			2,000	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Max.)	0.48	0.53	0.62	0.79	1.46	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. Insertion Loss is estimated as 0.1 dB for the MMCX connector and 0.2 dB for the SMA connector.

Mechanical Specifications

Cable Assembly

Length*	39.37 in [100 cm]
Diameter	0.315 in [8 mm]

Cable

Cable Type	LMR-100A
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel
Dielectric Type	PE
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PVC, Black
Jacket Diameter	0.11 in [2.79 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder PE3C1997LF-100CM](#)



MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3C1997LF-100CM

One Time Minimum Bend Radius	0.25 in [6.35 mm]
Repeated Minimum Bend Radius	1 in [25.4 mm]
Bending Moment	0.1 lbs-ft [0.14 N-m]
Flat Plate Crush	10 lbs/in [0.18 Kg/mm]
Tensile Strength	15 lbs [6.8 Kg]

Connectors

Description	Connector 1	Connector 2
Type	MMCX Plug	SMA Male Right Angle
Specification	BS EN 122340	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 μ in minimum	50 μ in minimum
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating	Brass, Gold	
Outer Conductor Plating Specification	3 μ in minimum	
Body Material and Plating	Brass, Gold	Brass, Nickel
Body Plating Specification	3 μ in minimum	100 μ in minimum
Coupling Nut Material and Plating		Brass, Nickel
Coupling Nut Plating Specification		100 μ in minimum
Hex Size		5/16 inch
Torque		3 in-lbs [0.34 Nm]

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder PE3C1997LF-100CM](#)



MMCX Plug to SMA Male Right Angle Cable 100 cm
Length Using LMR-100 Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3C1997LF-100CM

How to Order

Part Number Configuration:

PE3C1997LF - xx uu

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length
Base Number

Example: PE3C1997LF-12 = 12 inches long cable
PE3C1997LF-100cm = 100 cm long cable

MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMA Male Right Angle Cable 100 cm Length Using LMR-100 Coax , LF Solder PE3C1997LF-100CM](#)

URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C1997LF-100CM CAD Drawing
 MMCX Plug to SMA Male Right Angle Cable 100 cm
 Length Using LMR-100 Coax , LF Solder

REVISIONS				
REV.	DESCRIPTION	DATE	APPROVED	
A	INITIAL RELEASE	8/20/2020	S.SELLIS	



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		TOLERANCES:		THIRD-ANGLE PROJECTION	
X = ± 2	[.08]	FRACTIONS	$\pm 1/32$		
XX = $\pm .02$	[.51]	ANGLES $\pm 1^\circ$			
XXX = $\pm .005$	[.13]	CABLE LENGTH (L) TOLERANCES:			
		L \leq 12 [305] = $+1 [25]$ / -0			
		12 [305] < L \leq 60 [1524] = $+2 [51]$ / -0			
		60 [1524] < L \leq 120 [3048] = $+4 [102]$ / -0			
		120 [3048] < L \leq 300 [7620] = $+6 [152]$ / -0			
		300 [7620] < L = $+5\% L$ / -0			
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.					
THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.		SHEET 1 OF 1		SCALE N/A	
SIZE A		ITEM NO. PE3C1997LF	REV A		
CAGE CODE 53919		DRAWN BY K.DANG			