



## SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax

### RF Cable Assemblies Technical Data Sheet


**PE3C2486**

#### Configuration

- Connector 1: SMA Male
- Connector 2: SMA Male
- Cable Type: LMR-240-UF

#### Features

- Max Frequency 5.8 GHz
- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- TPE Jacket
- 500 Mating Cycles



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE3C2486 SMA male to SMA male cable using LMR-240-UF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMA to SMA cable assembly has a male to male gender configuration with 50 ohm flexible LMR-240-UF coax. The PE3C2486 SMA male to SMA male cable assembly operates to 5.8 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax PE3C2486](#)



## SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax

### RF Cable Assemblies Technical Data Sheet

**PE3C2486**

#### Electrical Specifications

| Description                   | Minimum | Typical      | Maximum | Units                            |
|-------------------------------|---------|--------------|---------|----------------------------------|
| Frequency Range               | DC      |              | 5.8     | GHz                              |
| VSWR                          |         |              | 1.4:1   |                                  |
| Velocity of Propagation       |         | 84           |         | %                                |
| RF Shielding                  | 90      |              |         | dB                               |
| Group Delay                   |         | 1.21 [3.97]  |         | ns/ft [ns/m]                     |
| Capacitance                   |         | 24.2 [79.4]  |         | pF/ft [pF/m]                     |
| Inductance                    |         | 0.06 [0.2]   |         | uH/ft [uH/m]                     |
| DC Resistance Inner Conductor |         | 4.28 [14.04] |         | $\Omega$ /1000ft [ $\Omega$ /Km] |
| DC Resistance Outer Conductor |         | 3.89 [12.76] |         | $\Omega$ /1000ft [ $\Omega$ /Km] |
| Jacket Spark                  |         |              | 5,000   | Vrms                             |

#### Specifications by Frequency

| Description           | F1    | F2    | F3    | F4    | F5    | Units |
|-----------------------|-------|-------|-------|-------|-------|-------|
| Frequency             | 0.25  | 0.5   | 1     | 2.5   | 5.8   | GHz   |
| Insertion Loss (Typ.) | 0.046 | 0.066 | 0.095 | 0.155 | 0.244 | dB/ft |
|                       | 0.15  | 0.22  | 0.31  | 0.51  | 0.8   | dB/m  |

#### Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.1 dB per connector.

#### Mechanical Specifications

##### Cable Assembly

Weight 0.058 lbs [26.31 g]

##### Cable

Cable Type LMR-240-UF  
 Impedance 50 Ohms  
 Inner Conductor Type Stranded  
 Inner Conductor Material and Plating Copper  
 Dielectric Type PE (F)  
 Number of Shields 2  
 Shield Layer 1 Aluminum Tape  
 Shield Layer 2 Tinned Copper Braid  
 Jacket Material TPE, Black  
 Jacket Diameter 0.24 in [6.1 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax PE3C2486](#)



## SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax

### RF Cable Assemblies Technical Data Sheet

**PE3C2486**

|                              |                        |
|------------------------------|------------------------|
| One Time Minimum Bend Radius | 0.75 in [19.05 mm]     |
| Repeated Minimum Bend Radius | 2.5 in [63.5 mm]       |
| Bending Moment               | 0.13 lbs-ft [0.18 N-m] |
| Flat Plate Crush             | 13 lbs/in [0.23 Kg/mm] |
| Tensile Strength             | 80 lbs [36.29 Kg]      |

#### Connectors

| Description                       | Connector 1        | Connector 2        |
|-----------------------------------|--------------------|--------------------|
| Type                              | SMA Male           | SMA Male           |
| Impedance                         | 50 Ohms            | 50 Ohms            |
| Mating Cycles                     | 500                | 500                |
| Contact Material and Plating      | Brass, Gold        | Brass, Gold        |
| Dielectric Type                   | PTFE               | PTFE               |
| Body Material and Plating         | Brass, Gold        | Brass, Gold        |
| Coupling Nut Material and Plating | Brass, Gold        | Brass, Gold        |
| Hex Size                          | 5/16 inch          | 5/16 inch          |
| Torque                            | 3 in-lbs [0.34 Nm] | 3 in-lbs [0.34 Nm] |

#### Environmental Specifications

##### Temperature

|                 |                  |
|-----------------|------------------|
| Operating Range | -40 to +85 deg C |
|-----------------|------------------|

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax PE3C2486](#)



## SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax

### RF Cable Assemblies Technical Data Sheet

**PE3C2486**

#### How to Order

Part Number Configuration:

**PE3C2486**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C2486-12 = 12 inches long cable  
PE3C2486-100cm = 100 cm long cable

SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax PE3C2486](https://www.pasternack.com/sma-male-to-sma-male-low-loss-cable-using-lmr-240-uf-pe3c2486-p.aspx)

URL: <https://www.pasternack.com/sma-male-to-sma-male-low-loss-cable-using-lmr-240-uf-pe3c2486-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C2486 CAD Drawing

SMA Male to SMA Male Low Loss Cable Using LMR-240-UF Coax

