

TNC Male to TNC Female Bulkhead Low Loss Cable  
24 Inch Length Using LMR-100 Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet


PE3C7630/HS-24

**Configuration**

- Connector 1: TNC Male
- Connector 2: TNC Female Bulkhead
- Cable Type: LMR-100A

**Features**

- Max Frequency 1 GHz
- Shielding Effectivity > 90 dB
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



**Applications**

- General Purpose
- Laboratory Use

**Description**

Pasternack's PE3C7630/HS-24 TNC male to TNC female bulkhead 24 inch cable using LMR-100 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to TNC cable assembly has a male to female gender configuration with 50 ohm flexible LMR-100A coax. The PE3C7630/HS-24 TNC male to TNC female cable assembly operates to 1 GHz. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink PE3C7630/HS-24](#)

## TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink



### RF Cable Assemblies Technical Data Sheet

**PE3C7630/HS-24**

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1,000	MHz
VSWR			1.4:1	
Velocity of Propagation		66		%
RF Shielding	90			dB
Group Delay		1.54 [5.05]		ns/ft [ns/m]
Capacitance		30.8 [101.05]		pF/ft [pF/m]
Inductance		0.077 [0.25]		uH/ft [uH/m]
DC Resistance Inner Conductor		81 [265.75]		Ω/1000ft [Ω/Km]
DC Resistance Outer Conductor		9.5 [31.17]		Ω/1000ft [Ω/Km]
Jacket Spark			2,000	Vrms

#### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	500	1,000	MHz
Insertion Loss (Typ.)	0.3	0.34	0.44	0.54	0.68	dB

#### Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

#### Mechanical Specifications

##### Cable Assembly

Length*	24 in [609.6 mm]
Diameter	0.689 in [17.5 mm]

##### Cable

Cable Type	LMR-100A
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel
Dielectric Type	PE
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PVC, Black
Jacket Diameter	0.11 in [2.79 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink PE3C7630/HS-24](#)

## TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink



### RF Cable Assemblies Technical Data Sheet

PE3C7630/HS-24

One Time Minimum Bend Radius	0.25 in [6.35 mm]
Repeated Minimum Bend Radius	1 in [25.4 mm]
Bending Moment	0.1 lbs-ft [0.14 N-m]
Flat Plate Crush	10 lbs/in [0.18 Kg/mm]
Tensile Strength	15 lbs [6.8 Kg]

#### Connectors

Description	Connector 1	Connector 2
Type	TNC Male	TNC Female Bulkhead
Specification		MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Brass, Gold
Contact Plating Specification	15 $\mu$ in	30 $\mu$ in minimum
Dielectric Type	Teflon	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 $\mu$ in	100 $\mu$ in minimum
Coupling Nut Material and Plating	Brass, Nickel	
Coupling Nut Plating Specification	100 $\mu$ in	

#### Environmental Specifications

##### Temperature

Operating Range

-40 to +85 deg C

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink PE3C7630/HS-24](#)

TNC Male to TNC Female Bulkhead Low Loss Cable  
24 Inch Length Using LMR-100 Coax with HeatShrink




RF Cable Assemblies Technical Data Sheet

PE3C7630/HS-24

**How to Order**

Part Number Configuration:



Example: PE3C7630/HS-12 = 12 inches long cable  
PE3C7630/HS-100cm = 100 cm long cable

TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch Length Using LMR-100 Coax with HeatShrink PE3C7630/HS-24](#)

URL: <https://www.pasternack.com/tnc-male-tnc-female-lmr100-cable-assembly-pe3c7630-hs-24-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3C7630/HS-24 CAD Drawing

TNC Male to TNC Female Bulkhead Low Loss Cable 24 Inch  
Length Using LMR-100 Coax with HeatShrink

