

## MCX Jack Bulkhead to Trimmed Lead Cable 9 Inch Length Using RG178 Coax with HeatShrink




### PE3C9204/HS-9

#### Configuration

- Connector 1: MCX Jack Bulkhead
- Connector 2: Trimmed Lead
- Cable Type: RG178
- Coax Flex Type: Flexible

#### Features

- 70% Phase Velocity
- FEP Jacket



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE3C9204/HS-9 50 ohm MCX jack bulkhead to trimmed lead 9 inch cable using RG178 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. Our RF cable assembly with MCX bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

#### Mechanical Specifications

##### Cable Assembly

Length	9 in [228.6 mm]
Width/Diameter	0.5 in [12.7 mm]
Weight	0.008 lbs [3.63 g]

##### Cable

Cable Type	RG178
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel, Silver

## MCX Jack Bulkhead to Trimmed Lead Cable 9 Inch Length Using RG178 Coax with HeatShrink



### PE3C9204/HS-9

Dielectric Type	PTFE
Number of Shields	1
Shield Layer 1	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.072 in [1.83 mm]
Repeated Minimum Bend Radius	0.4 in [10.16 mm]

### Connectors

Description	Connector 1	Connector 2
Type	MCX Jack Bulkhead	Trimmed Lead
Specification	MIL-C-39012	
Impedance	50 Ohms	0 Ohms
Configuration	Straight	Straight
Mating Cycles	500	
Contact Material and Plating	Beryllium Copper, Gold over Nickel	
Contact Plating Specification	30 µin minimum	
Dielectric Type	PTFE	
Body Material and Plating	Brass, Nickel	
Body Plating Specification	100 µin minimum	

### Environmental Specifications

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

## MCX Jack Bulkhead to Trimmed Lead Cable 9 Inch Length Using RG178 Coax with HeatShrink



### PE3C9204/HS-9

#### Typical Performance Data

#### How to Order

Part Number Configuration:

**PE3C9204/HS - xx uu**

\_\_\_\_\_ Unit of Measure:  
 cm = Centimeters  
 <blank> = Inches  
 \_\_\_\_\_ Length  
 \_\_\_\_\_ Base Number

Example: PE3C9204/HS-12 = 12 inches long cable  
 PE3C9204/HS-100cm = 100 cm long cable

MCX Jack Bulkhead to Trimmed Lead Cable 9 Inch Length Using RG178 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Jack Bulkhead to Trimmed Lead Cable 9 Inch Length Using RG178 Coax with HeatShrink PE3C9204/HS-9](https://www.pasternack.com/mcx-jack-bulkhead-to-trimmed-lead-cable-9-inch-length-using-rg178-with-heatshrink-pe3c9204-hs-9)

URL: <https://www.pasternack.com/mcx-jack-bulkhead-to-trimmed-lead-cable-9-inch-length-using-rg178-with-heatshrink-pe3c9204-hs-9-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

# PE3C9204/HS-9 CAD Drawing

MCX Jack Bulkhead to Trimmed Lead Cable 9 Inch Length Using RG178 Coax with HeatShrink

