



## 10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax

### RF Cable Assemblies Technical Data Sheet

**PE3C9764**

#### Configuration

- Connector 1: 10KV Male
- Connector 2: 10KV Female Bulkhead
- Cable Type: RG303HV

#### Features

- 69% Phase Velocity
- FEP Jacket
- Voltage rating of 10KV
- Recessed Contacts

#### Applications

- General Purpose
- Laboratory Use
- High voltage power supplies/ Amplifiers
- Nuclear instrumentation
- Test and measurement equipment

#### Description

Pasternack's PE3C9764 10KV male to 10KV female bulkhead cable using RG303HV coax is part of our full line of RF components available for same-day shipping. This Pasternack 10KV to 10KV cable assembly has a male to female gender configuration with 50 ohm RG303HV coax. Our RF cable assembly with 10KV bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. Our 10kV high voltage RF cable assemblies are designed to handle higher voltages and minimize the risk of electric shock. Both the connectors used in this cable assemblies have recessed contact design to withstand unmated higher voltage. These cable assemblies are commonly used in applications where high voltage transmission and RF signal integrity are critical. These cable assemblies are constructed with high-quality insulation materials capable of withstanding higher voltages, ensuring safety and preventing electrical breakdown. Our cable assemblies are built with durable and flexible materials to withstand harsh environmental conditions and repetitive movements, ensuring reliable performance over extended periods.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation	69			%
Operating Voltage (DC)			10,000	Vdc
Test Voltage (DC)			15,000	V

Electrical Specification Notes:  
Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax PE3C9764](#)



## 10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax

### RF Cable Assemblies Technical Data Sheet

**PE3C9764**

#### Mechanical Specifications

##### Cable Assembly

Weight	0.126 lbs [57.15 g]
<b>Cable</b>	
Cable Type	RG303HV
Impedance	50 Ohms
Inner Conductor Material and Plating	Silver, Copper Clad Aluminum
Dielectric Type	FEP
Number of Shields	1
Jacket Material	FEP
Jacket Diameter	0.169 in [4.29 mm]
Repeated Minimum Bend Radius	0.788 in [20.02 mm]

##### Connectors

Description	Connector 1	Connector 2
Type	10KV Male	10KV Female Bulkhead Bayonet
Specification	MIL-STD-202	MIL-STD-202
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold/Tri-Metal	Brass, Gold/Tri-Metal
Dielectric Type	PE (HD)	PE (HD)
Body Material and Plating	Brass, Nickel Over Copper	Brass, Tinned Copper
Coupling Nut Material and Plating	Brass, Nickel Over Copper	Brass, Tinned Copper

#### Compliance Certifications (see product page for current document)

#### Plotted and Other Data

##### Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax PE3C9764](#)

10KV Male to 10KV Female Bulkhead  
Cable Using RG303HV Coax



## RF Cable Assemblies Technical Data Sheet

**PE3C9764**

### How to Order

Part Number Configuration:

**PE3C9764**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C9764-12 = 12 inches long cable  
PE3C9764-100cm = 100 cm long cable

10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax PE3C9764](#)

URL: <https://www.pasternack.com/10kv-male-to-10kv-female-bulkhead-cable-using-rg303hv-pe3c9764-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3C9764 CAD Drawing

10KV Male to 10KV Female Bulkhead Cable Using RG303HV Coax

