

TNC Male Right Angle to TNC Female Bulkhead Low Loss Cable Using LMR-195-UF Coax



PE3C9905

Configuration

- Connector 1: TNC Male Right Angle
- Connector 2: TNC Female Bulkhead
- Cable Type: LMR-195-UF
- Coax Flex Type: Flexible

Features

- Max Frequency 3 MHz
- Shielding Effectivity > 90 dB
- 74% Phase Velocity
- Double Shielded
- TPE Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C9905 TNC male right angle to TNC female bulkhead cable using LMR-195-UF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to TNC cable assembly has a male to female gender configuration with 50 ohm flexible LMR-195-UF coax. The PE3C9905 TNC male to TNC female cable assembly operates to 3 MHz. The right angle TNC interface on the LMR-195-UF cable allows for easier connections in tight spaces. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-------------------------------|---------|--------------|---------|-----------------------|
| Frequency Range | DC | | 3 | GHz |
| VSWR | | | 1.35:1 | |
| Velocity of Propagation | | 74 | | % |
| RF Shielding | 90 | | | dB |
| Group Delay | | 1.27 [4.17] | | ns/ft [ns/m] |
| Capacitance | | 25.4 [83.33] | | pF/ft [pF/m] |
| Inductance | | 0.064 [0.21] | | uH/ft [uH/m] |
| DC Resistance Inner Conductor | | 9.5 [31.17] | | Ohms/1000ft [Ohms/Km] |
| DC Resistance Outer Conductor | | 4.9 [16.08] | | Ohms/1000ft [Ohms/Km] |
| Operating Voltage (AC) | | | 500 | Vrms |

TNC Male Right Angle to TNC Female Bulkhead
Low Loss Cable Using LMR-195-UF Coax



PE3C9905

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|--------------|---------|---------|---------|-------|
| Jacket Spark | | | 3,000 | Vrms |

Specifications by Frequency

| Part Number | Length | Description | F1 | F2 | F3 | F4 | F5 | Units | Weight (lbs) |
|--------------|--------------------------|-----------------------|-----------|-------|-------|-------|-------|-------|--------------|
| | | | Frequency | | | | | MHz | |
| PE3C9905 | Custom Lengths Available | Insertion Loss (Typ.) | 0.042 | 0.068 | 0.097 | 0.132 | 0.246 | dB/ft | |
| | | | 0.14 | 0.23 | 0.32 | 0.44 | 0.81 | dB/m | |
| PE3C9905-12 | 12 Inch | Insertion Loss (Typ.) | 0.35 | 0.37 | 0.4 | 0.44 | 0.55 | dB | 0.115 |
| PE3C9905-24 | 24 Inch | Insertion Loss (Typ.) | 0.39 | 0.44 | 0.5 | 0.57 | 0.8 | dB | 0.136 |
| PE3C9905-36 | 36 Inch | Insertion Loss (Typ.) | 0.43 | 0.51 | 0.6 | 0.7 | 1.04 | dB | 0.157 |
| PE3C9905-60 | 60 Inch | Insertion Loss (Typ.) | 0.51 | 0.64 | 0.79 | 0.96 | 1.53 | dB | 0.199 |
| PE3C9905-300 | 300 Inch | Insertion Loss (Typ.) | 1.35 | 2 | 2.73 | 3.6 | 6.45 | dB | 0.619 |

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

| | |
|-----------------------------|----------------|
| Loss due to Connector 1: | 0.2 dB |
| Loss due to Connector 2: | 0.1 dB |
| Base Weight: | 0.115 pounds |
| Additional Weight per Inch: | 0.00175 pounds |

Electrical Specification Notes:
Values at 25°C, sea level.

Mechanical Specifications

Cable Assembly

| | |
|----------------|---------------------|
| Width/Diameter | 0.5 in [12.7 mm] |
| Weight | 0.094 lbs [42.64 g] |

Cable

| | |
|--------------------------------------|------------------------|
| Cable Type | LMR-195-UF |
| Impedance | 50 Ohms |
| Inner Conductor Type | Stranded |
| Inner Conductor Material and Plating | Copper |
| Dielectric Type | Foam PE |
| Number of Shields | 2 |
| Shield Layer 1 | Aluminum Tape |
| Shield Layer 2 | Tinned Copper |
| Jacket Material | TPE, Black |
| Jacket Diameter | 0.195 in [4.95 mm] |
| One Time Minimum Bend Radius | 0.5 in [12.7 mm] |
| Repeated Minimum Bend Radius | 2 in [50.8 mm] |
| Bending Moment | 0.1 lbs-ft [0.14 N-m] |
| Flat Plate Crush | 10 lbs/in [0.18 Kg/mm] |
| Tensile Strength | 40 lbs [18.14 Kg] |

TNC Male Right Angle to TNC Female Bulkhead
Low Loss Cable Using LMR-195-UF Coax



PE3C9905

Connectors

| Description | Connector 1 | Connector 2 |
|------------------------------------|----------------------|---------------------|
| Type | TNC Male Right Angle | TNC Female Bulkhead |
| Specification | MIL-STD-348A | MIL-STD-348A |
| Impedance | 50 Ohms | 50 Ohms |
| Configuration | Right Angle | Straight |
| Contact Material and Plating | Brass, Gold | Brass, Gold |
| Contact Plating Specification | 30 µin minimum | 30 µin minimum |
| Dielectric Type | PTFE | PTFE |
| Body Material and Plating | Brass, Nickel | Brass, Nickel |
| Body Plating Specification | 100 µin minimum | 100 µin minimum |
| Coupling Nut Material and Plating | Brass, Nickel | |
| Coupling Nut Plating Specification | 100 µin minimum | |

Environmental Specifications

Operating Range Temperature -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:
Values at 25°C, sea level.

TNC Male Right Angle to TNC Female Bulkhead Low Loss Cable Using LMR-195-UF Coax



PE3C9905

Typical Performance Data

How to Order

Part Number Configuration:

PE3C9905

- xx

uu

Unit of Measure:

cm = Centimeters

<blank> = Inches

Length

Base Number

Example: PE3C9905-12 = 12 inches long cable
PE3C9905-100cm = 100 cm long cable

TNC Male Right Angle to TNC Female Bulkhead Low Loss Cable Using LMR-195-UF Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Right Angle to TNC Female Bulkhead Low Loss Cable Using LMR-195-UF Coax PE3C9905](#)

URL: <https://www.pasternack.com/tnc-male-right-angle-to-tnc-female-bulkhead-low-loss-cable-using-lmr-195-uf-pe3c9905-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3C9905 CAD Drawing

TNC Male Right Angle to TNC Female Bulkhead Low Loss Cable Using LMR-195-UF Coax



NOTES:

1. CABLE ASSEMBLY LENGTH LABEL PLACEMENT: 36 INCHES OR LESS, ONE LABEL APPROXIMATELY CENTERED, LONGER THAN 36 INCHES, TWO LABELS APPROXIMATELY 6 INCHES FROM EACH CONNECTOR.
2. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
3. CABLE ASSEMBLY LENGTH DETERMINED BY ITEM PN AND DESCRIPTION.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE ARE BEING EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVISION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE IN INCHES. DIMENSIONS IN [] ARE MILLIMETERS.

TOLERANCES:

.X = ±.2 [5]
 .XX = ±.02 [0.5] ±.132
 .XXX = ±.005 [0.13] ANGLES ± 1°

CABLE LENGTH TOLERANCES:

<12 [305] ≤ 60 [1524] = +1 [25] / -0
 >60 [1524] ≤ 120 [3048] = +4 [102] / -0
 >120 [3048] ≤ 300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY. UNDIMENSIONED NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION. COLORS MAY VARY.

| | | | |
|---|-------|--|----------|
| | | INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 | |
| Website: www.Pasternack.com Phone: 1.866.727.8376 1.949.261.1920 | | SCALE | NONE |
| DESCRIPTION TNC MALE RIGHT ANGLE TO TNC FEMALE BULKHEAD CABLE USING LMR-195-UF COAX | | SHEET | 1 OF 1 |
| SIZE | A | CAGE CODE | HBAKKE |
| ITEM NO. | 53919 | ITEM NO. | PE3C9905 |
| REV | A | REV | A |