


## BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin Cable Using PE- P141 Coax with HeatShrink, LF Solder



### PE3M0364

#### Configuration

- Connector 1: Push-on BMA Pin
- Connector 2: Push-on BMA Pin
- Cable Type: PE-P141
- Coax Flex Type: Flexible



#### Features

- Max Frequency: 18 GHz
- Can be installed in all D38999 size 8 inserts
- Lot traceability
- High speed RF cable assembly

#### Applications

- Military and Aerospace
- Avionics
- Industrial Automation

#### Description

The PE3M0364 from Pasternack is a D38999 contact cable assembly that is built with a size 8 BMA pin contact connection on one end and a BMA pin connector on the other. Pasternack MIL-DTL-38999 (also known as D38999 or 38999) coaxial cable assembly products are used in applications requiring high quality such as laboratory RF test and measurement, rugged and designed for defense/military, production environments, general use, etc. This high frequency D38999 cable assembly operates at a maximum frequency of 18 GHz.

The PE3M0364 RF cable has a FEP jacket of 0.163-inch diameter. This radio frequency cable assembly can withstand temperatures ranging from -65 to 165 degrees C. Our BMA pin to BMA pin cable has a maximum VSWR of 1.4:1. This RF cable assembly with a 0.5-inch diameter has copper clad steel as the cable's inner conducting material and PTFE dielectric type. The PE3M0364 between-series RF cable has 0.8 inches of repeated minimum bend radius along with 110 dB of minimum RF shielding.

BMA pin to BMA pin cable assembly is built with PE-P141, which is a flexible coax type. The Pasternack PE3M0364 flexible cable assembly has a 50 Ohm impedance and is double shielded. Additional dimensions, specifications, and CAD drawings for this BMA to BMA RF cable are available on our downloadable PDF datasheet.

BMA pin to BMA pin cable assembly is just one of more than one million in-stock RF products available. Pasternack is where to buy high quality custom RF cable assembly products for rugged and MIL-STD designed military/defense, aerospace, outdoor and harsh environment, microwave and millimeter wave radio transmitter receiver, component inter-connection and more for RF test & measurement labs, telecom, phase stable, phase and delay matching, and other radio frequency applications can be manufactured. Variations of BMA cable assemblies can also be built and will ship on the same day as well, search this website or contact us for assistance. For further information on similar products, our expert technical support and trained sales team can get you the ideal BMA to BMA RF cable assembly as per your requirements.

## BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin Cable Using PE- P141 Coax with HeatShrink, LF Solder



### PE3M0364

#### Referenced Specifications

IPC J-STD-001	Requirements for Soldered Electrical and Electronic Assemblies
IPC J-STD-006	Requirements for Electronic Grade Solder Alloys and Fluxed and Non-Fluxed Solid Solders for Electronic Soldering Applications
IPC/WHMA-A-620	Requirements and Acceptance for Cable and Wire Harness Assemblies
MIL-DTL-17	Cables, Radio Frequency, Flexible and Semirigid, General Specification for
MIL-PRF-39012	Connectors, Coaxial, Radio Frequency, General Specification for
MIL-STD-348	Radio Frequency Connector Interfaces for MIL-DTL-3643, MIL-DTL-3650, MIL-DTL-3655, MIL-DTL-25516, MIL-PRF-31031, MIL-PRF-39012, MIL-PRF-49142, MIL-PRF-55339, MIL-DTL-83517
SAE AS22520	Crimping Tools, Wire Termination, General Specification For
SAE AS23053	Insulation Sleeving, Electrical, Heat Shrinkable, General Specifications For
SAE AS5942	Marking of Electrical Insulating Materials
IPC J-STD-001	Requirements for Soldered Electrical and Electronic Assemblies

#### Material Specifications

Component	Specification
Cable	PE-P141 in accordance with PE-P141 datasheet
Connector 1	in accordance with MIL-DTL-38999
Connector 2	in accordance with MIL-DTL-38999
Heat Shrink 1	M23053/5-106-0 in accordance with SAE AS23053
Heat Shrink 2	M23053/5-106-0 in accordance with SAE AS23053
Solder	SAC305 in accordance with J-STD-006

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.4:1	
Velocity of Propagation		70		%
RF Shielding	110			dB
Capacitance		29.4 [96.46]		pF/ft [pF/m]

#### Specifications by Frequency

## BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin Cable Using PE- P141 Coax with HeatShrink, LF Solder



### PE3M0364

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	1000	2000	4500	9000	18000	MHz	
PE3M0364	Custom Lengths Available	Insertion Loss (Typ.)	0.11	0.17	0.25	0.41	0.58	dB/ft	
			0.37	0.55	0.83	1.35	1.91	dB/m	
PE3M0364-6	6 inch	Insertion Loss (Typ.)	0.26	0.29	0.33	0.41	0.49	dB	0.0345
PE3M0364-12	12 inch	Insertion Loss (Typ.)	0.32	0.37	0.46	0.61	0.78	dB	0.049
PE3M0364-24	24 inch	Insertion Loss (Typ.)	0.43	0.53	0.71	1.02	1.36	dB	0.078
PE3M0364-36	36 inch	Insertion Loss (Typ.)	0.54	0.7	0.96	1.43	1.94	dB	0.107
PE3M0364-48	48 inch	Insertion Loss (Typ.)	0.65	0.86	1.21	1.84	2.52	dB	0.136
PE3M0364-60	60 inch	Insertion Loss (Typ.)	0.76	1.03	1.46	2.25	3.1	dB	0.165

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1 dB

Loss due to Connector 2: 0.1 dB

Base Weight: 0.049 pounds

Additional Weight per Foot: 0.029 pounds

#### Electrical Specification Notes:

Values at 25°C, sea level.

### Mechanical Specifications

#### Cable Assembly

Description	Minimum	Typical	Maximum	Units
Length*			0 [0]	in [mm]
Cable Outer Diameter		0.163		in
Weight		0.049 [22.23]		lbs [g]
Repeated Minimum Bend Radius	0.8			in

#### Cable Characteristics

Description	Specification
Cable Type	PE-P141
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Tape
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP

BMA Size 8 D38999 Contact Pin to BMA  
Size 8 D38999 Contact Pin Cable Using PE-  
P141 Coax with HeatShrink, LF Solder



## PE3M0364

### Connector Characteristics

Description	Connector 1	Connector 2
Type	BMA Pin	BMA Pin
Specification	MIL-DTL-38999	MIL-DTL-38999
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Connection Method	Push-on	Push-on
Contact Size	8	8
Mating Cycles	1,000	1,000
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating	Stainless Steel, Gold	Stainless Steel, Gold
Body Material and Plating	Stainless Steel, Gold	Stainless Steel, Gold

Mechanical Specification Notes:

### Environmental Specifications

Description	Specification
Temperature Operating Range	-65 to +165 deg C

### Compliance Certifications

(see product page for current document)

### Plotted and Other Data

Notes:

Values at 25°C, sea level.


## BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin Cable Using PE-P141 Coax with HeatShrink, LF Solder



### PE3M0364

#### How to Order

Part Number Configuration:



Example: PE3M0364-12 = 12 inches long cable  
 PE3M0364-100cm = 100 cm long cable

Cable Assembly Length Tolerances:

Imperial English		Metric	
"L" ≤ 1 ft	+0.5 in / -0 in	"L" ≤ 0.3 m	+12.5 mm / -0 mm
1 ft < "L" ≤ 5 ft	+1 in / -0 in	0.3 m < "L" ≤ 1.5 m	+25 mm / -0 mm
5 ft < "L" ≤ 10 ft	+2 in / -0 in	1.5 m < "L" ≤ 3 m	+50 mm / -0 mm
10 ft < "L" ≤ 25 ft	+3 in / -0 in	3 m < "L" ≤ 7.5 m	+75 mm / -0 mm
25 ft < "L"	+2%"L" / -0%"L"	7.5 m < "L"	+2%"L" / -0%"L"

\* Cable Length = "L"

BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin Cable Using PE-P141 Coax with HeatShrink, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin Cable Using PE-P141 Coax with HeatShrink, LF Solder PE3M0364](#)

URL: <https://www.pasternack.com/bma-8-contact-pin-to-bma-8-contact-pin-cable-using-pe-p141-coax-with-heatshrink-lf-solder-pe3m0364-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

# PE3M0364 CAD Drawing

BMA Size 8 D38999 Contact Pin to BMA Size 8 D38999 Contact Pin

Cable Using PE-P141 Coax with HeatShrink, LF Solder

