

MCX Plug Right Angle to SMA Female Bulkhead Cable
100 CM Length Using PE-SR405FLJ Coax , LF Solder




RF Cable Assemblies Technical Data Sheet

PE3W09085LF/HS-100CM


Configuration

- Connector 1: MCX Plug Right Angle
- Connector 2: SMA Female Bulkhead
- Cable Type: PE-SR405FLJ



Features

- Max Frequency 6 GHz
- Shield Effectivity > 100 dB
- 69.5% Phase Velocity
- FEP Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W09085LF/HS-100CM MCX plug right angle to SMA female bulkhead 100 cm cable using PE-SR405FLJ coax is part of our full line of RF components available for same-day shipping. Pasternack's formable RF cable assemblies provide an alternative to costly pre-formed semi-rigid assemblies since they are hand formable. This Pasternack MCX to SMA cable assembly has a plug to female gender configuration with 50 ohm formable PE-SR405FLJ coax. The PE3W09085LF/HS-100CM MCX plug to SMA female cable assembly operates to 6 GHz. The right angle MCX interface on the PE-SR405FLJ cable allows for easier connections in tight spaces. Our RF cable assembly with SMA bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM Length Using PE-SR405FLJ Coax , LF Solder PE3W09085LF/HS-100CM](#)



MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM Length Using PE-SR405FLJ Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W09085LF/HS-100CM

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
Velocity of Propagation		69.5		%
RF Shielding	100			dB
Group Delay		1.43 [4.69]		ns/ft [ns/m]
Capacitance		29 [95.14]		pF/ft [pF/m]
DC Resistance Inner Conductor		65.7 [215.55]		Ω/1000ft [Ω/Km]
DC Resistance Outer Conductor		10.2 [33.46]		Ω/1000ft [Ω/Km]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	6	GHz
Insertion Loss (Typ.)	0.56	0.79	1.03	1.43	2.27	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB for the straight connector and 0.2 dB for the right angle connector.

Mechanical Specifications

Cable Assembly

Length* 39.37 in [100 cm]

Cable

Cable Type PE-SR405FLJ
Impedance 50 Ohms
Inner Conductor Type Solid
Inner Conductor Material and Plating Copper Clad Steel, Silver
Dielectric Type PTFE
Number of Shields 1
Outer Conductor Material and Plating Tinned Copper Composite Braid
Jacket Material FEP, Black
Jacket Diameter 0.105 in [2.67 mm]

One Time Minimum Bend Radius 0.5 in [12.7 mm]
Repeated Minimum Bend Radius 0.787 in [19.99 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM Length Using PE-SR405FLJ Coax , LF Solder PE3W09085LF/HS-100CM](#)



MCX Plug Right Angle to SMA Female Bulkhead Cable
100 CM Length Using PE-SR405FLJ Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W09085LF/HS-100CM

Connectors

Description	Connector 1	Connector 2
Type	MCX Plug Right Angle	SMA Female Bulkhead
Specification		MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold over Nickel	Beryllium Copper, Gold
Contact Plating Specification		50 μ in minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Gold over Nickel	Stainless Steel, Gold
Body Plating Specification		30 μ in minimum

Environmental Specifications

Temperature

Operating Range

-55 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM Length Using PE-SR405FLJ Coax , LF Solder PE3W09085LF/HS-100CM](#)



MCX Plug Right Angle to SMA Female Bulkhead Cable
100 CM Length Using PE-SR405FLJ Coax , LF Solder

RF Cable Assemblies Technical Data Sheet

PE3W09085LF/HS-100CM

How to Order

Part Number Configuration:

PE3W09085LF/HS - xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W09085LF/HS-12 = 12 inches long cable
PE3W09085LF/HS-100cm = 100 cm long cable

MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM Length Using PE-SR405FLJ Coax , LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM Length Using PE-SR405FLJ Coax , LF Solder PE3W09085LF/HS-100CM](#)

URL: <https://www.pasternack.com/mcx-plug-sma-female-pe-sr405flj-cable-assembly-pe3w09085lf-hs-100cm-p.aspx>



The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W09085LF/HS-100CM CAD Drawing

MCX Plug Right Angle to SMA Female Bulkhead Cable 100 CM

Length Using PE-SR405FLJ Coax , LF Solder

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	3/13/2020	S.ELLIS



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS		REV. A
TOLERANCES:		
X = ± .2 [5.08]		FRACTIONS
.XX = ± .02 [5.51]		± 1/32
XXX = ± .005 [1.31]		ANGLES ± 1°
CABLE LENGTH (L) TOLERANCES:		
L ≤ 12 [305] = +1 [25] / -0		
12 [305] < L ≤ 60 [1524] = +2 [51] / -0		
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0		
120 [3048] < L ≤ 300 [7620] = +6 [153] / -0		
300 [7620] < L = +5% L / -0		
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.		
THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.		
© 2019 Pasternack Enterprises All Rights Reserved		
PE3W09085LF/HS-100CM REV 1.0		
T-Rev.D		

