




SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax

RF Cable Assemblies Technical Data Sheet

PE3W09919


Configuration

- Connector 1: SMA Male Right Angle
- Connector 2: N Male Right Angle
- Cable Type: PE-P195



Features

- Max Frequency 12.4 GHz
- 70% Phase Velocity
- Triple Shielded
- FEP Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W09919 SMA male right angle to type N male right angle cable using PE-P195 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMA to type N cable assembly has a male to male gender configuration with 50 ohm flexible PE-P195 coax. The PE3W09919 SMA male to type N male cable assembly operates to 12.4 GHz. The right angle SMA and right angle type N interfaces on the PE-P195 cable allow for easier connections in tight spaces. The triple shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax PE3W09919](#)



SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax

RF Cable Assemblies Technical Data Sheet

PE3W09919

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
VSWR			1.45:1	
Velocity of Propagation		70		%
Capacitance		29 [95.14]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.5	1	2.5	5	12.4	GHz
Insertion Loss (Typ.)	0.09	0.13	0.2	0.32	0.51	dB/ft
	0.3	0.43	0.66	1.05	1.67	dB/m

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.2 dB per connector.

Mechanical Specifications

Cable Assembly

Diameter 0.71 in [18.03 mm]

Cable

Cable Type PE-P195
 Impedance 50 Ohms
 Inner Conductor Type Solid
 Inner Conductor Material and Plating Copper Clad Steel, Silver PTFE
 Dielectric Type 3
 Number of Shields Silver Plated Copper Braid
 Shield Layer 1 Aluminum Tape
 Shield Layer 2 Silver Plated Copper Braid
 Shield Layer 3 FEP, Tan
 Jacket Material 0.195 in [4.95 mm]
 Jacket Diameter

Repeated Minimum Bend Radius

1 in [25.4 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax PE3W09919](#)



SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax

RF Cable Assemblies Technical Data Sheet

PE3W09919

Connectors

Description	Connector 1	Connector 2
Type	SMA Male Right Angle	N Male Right Angle
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	50 μ in minimum	
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Tri-Metal
Body Plating Specification	100 μ in minimum	
Coupling Nut Material and Plating	Brass, Nickel	Brass, Tri-Metal
Coupling Nut Plating Specification	100 μ in minimum	
Hex Size	5/16 inch	
Torque	3 in-lbs [0.34 Nm]	

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax PE3W09919](#)

SMA Male Right Angle to N Male Right Angle
Low Loss Cable Using PE-P195 Coax



RF Cable Assemblies Technical Data Sheet

PE3W09919

How to Order

Part Number Configuration:

PE3W09919

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W09919-12 = 12 inches long cable
PE3W09919-100cm = 100 cm long cable

SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax PE3W09919](https://www.pasternack.com/sma-male-n-male-pe-p195-cable-assembly-pe3w09919-p.aspx)

URL: <https://www.pasternack.com/sma-male-n-male-pe-p195-cable-assembly-pe3w09919-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W09919 CAD Drawing

SMA Male Right Angle to N Male Right Angle Low Loss Cable Using PE-P195 Coax

