

75 Ohm BNC Female Bulkhead to 75 Ohm BNC Male Cable Using 75 Ohm RG179 Coax, LF Solder



PE3W12699LF

Configuration

- Connector 1: BNC Female Bulkhead
- Connector 2: BNC Male
- Cable Type: RG179
- Coax Flex Type: Flexible

Features

- 70% Phase Velocity
- FEP Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W12699LF 75 ohm BNC female bulkhead to 75 ohm BNC male cable using 75 ohm RG179 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to BNC cable assembly has a female to male gender configuration with 75 ohm flexible RG179 coax. Our RF cable assembly with BNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		70		%
Capacitance		19.4 [63.65]		pF/ft [pF/m]

Mechanical Specifications

Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.028 lbs [12.7 g]

Cable

Cable Type	RG179
Impedance	75 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	1
Shield Layer 1	Silver Plated Copper Braid

75 Ohm BNC Female Bulkhead to 75 Ohm BNC Male Cable Using 75 Ohm RG179 Coax, LF Solder



PE3W12699LF

Jacket Material	FEP, Tan
Jacket Diameter	0.1 in [2.54 mm]
Repeated Minimum Bend Radius	0.4 in [10.16 mm]

Connectors

Description	Connector 1	Connector 2
Type	BNC Female Bulkhead	BNC Male
Impedance	75 Ohms	75 Ohms
Configuration	Straight	Straight
Contact Material and Plating		Brass, Gold
Contact Plating Specification		30 µin minimum
Dielectric Type		PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification		100 µin minimum
Coupling Nut Material and Plating		Brass, Nickel
Coupling Nut Plating Specification		100 µin minimum

Environmental Specifications

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

75 Ohm BNC Female Bulkhead to 75 Ohm BNC Male Cable Using 75 Ohm RG179 Coax, LF Solder



PE3W12699LF

Typical Performance Data

How to Order

Part Number Configuration: **PE3W12699LF** - **xx** **uu**

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length

Base Number

Example: PE3W12699LF-12 = 12 inches long cable
PE3W12699LF-100cm = 100 cm long cable

75 Ohm BNC Female Bulkhead to 75 Ohm BNC Male Cable Using 75 Ohm RG179 Coax, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm BNC Female Bulkhead to 75 Ohm BNC Male Cable Using 75 Ohm RG179 Coax, LF Solder PE3W12699LF](https://www.pasternack.com/75-ohm-bnc-female-bulkhead-to-75-ohm-bnc-male-cable-using-rg179-lf-solder-pe3w12699lf-p.aspx)

URL: <https://www.pasternack.com/75-ohm-bnc-female-bulkhead-to-75-ohm-bnc-male-cable-using-rg179-lf-solder-pe3w12699lf-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W12699LF CAD Drawing
75 Ohm BNC Female Bulkhead to 75 Ohm BNC Male Cable Using 75 Ohm RG179 Coax, LF Solder

