



# 0 to 100 dB Rotary Step Attenuator, BNC Female To BNC Female With 10 dB Step Rated To 1 Watt Up To 2 GHz

#### TECHNICAL DATA SHEET

PE7034-5

· See Notes regarding attenuation accuracy data

Configuration

Design Step, Bidirectional Attenuator
Connector 1 BNC Female
Connector 2 BNC Female

Body Material and Plating Aluminum

**Electrical Specifications** 

Frequency Range, GHz
Impedance, Ohms
50
Attenuation Value, dB
0 to 100
Step Size, dB
10
Step Type
Rotary
Maximum Input Power, Watts
1
Maximum VSWR
DC to 2
Impedance, Ohms
50
Rot 100
Rotary
1.5:1

Frequency 1

 Range, MHz
 DC to 1,000

 VSWR
 1.3:1

 Attenuation Accuracy, dB
 ± 1.5

Frequency 2

Range, GHz 1 to 2 VSWR 1.5:1 Attenuation Accuracy, dB ± 2

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -20 to +85

Size

 Length, in [mm]
 4.5 [114.3]

 Width, in [mm]
 4 [101.6]

 Height, in [mm]
 4 [101.6]

Connector 1

Type BNC Female Outer Conductor Material and Plating Aluminum

Connector 2

Type BNC Female

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 0 to 100 dB Rotary Step Attenuator, BNC Female To BNC Female With 10 dB Step Rated To 1 Watt Up To 2 GHz PE7034-5

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





# 0 to 100 dB Rotary Step Attenuator, BNC Female To BNC Female With 10 dB Step Rated To 1 Watt Up To 2 GHz

#### TECHNICAL DATA SHEET

PE7034-5

**Compliance Certifications** (visit www.Pasternack.com for current document)
REACH Compliant 06/18/2012

**Plotted and Other Data** 

Notes:

Values at 25 °C, sea level Attenuation Accuracy is + / - 0.5dB or 3%

0 to 100 dB Rotary Step Attenuator, BNC Female To BNC Female With 10 dB Step Rated To 1 Watt Up To 2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 0 to 100 dB Rotary Step Attenuator, BNC Female To BNC Female With 10 dB Step Rated To 1 Watt Up To 2 GHz PE7034-5

URL: http://www.pasternack.com/100db-step-bnc-female-bnc-female-1-watt-attenuator-pe7034-5-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

### PE7034-5 CAD Drawing

0 to 100 dB Rotary Step Attenuator, BNC Female To BNC Female With 10 dB Step Rated To 1 Watt Up To 2 GHz

