



0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz

RF Step Attenuators Technical Data Sheet

PE70A1022

Features

- 10 dB steps from 0 to 70 dB Attenuation
- Rotary Dial Control
- ± 0.5 dB or 3% Attenuation Accuracy
- BNC Female Connectors
- -20°C to $+80^{\circ}\text{C}$ Operating Temperature

Applications

- Instrumentation
- Precision Measurements
- Prototyping and Characterization
- Production Systems

Description

The PE70A1022 is a Step Attenuator that has 70 dB of total attenuation with 10 dB step size and rotary dial design across a frequency range from DC to 2.2 GHz. The design is tried and true technology that offers exceptional performance characteristics that include 0.5 dB maximum insertion loss, and a maximum VSWR of 1.4:1 at 2.2 GHz. The design also features excellent attenuation accuracy with ± 0.4 dB typical at 2.2 GHz. The Chem film Aluminum alloy package has BNC Female connectors, and operates within the temperature range of -20°C to 80°C .

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.2	GHz
Impedance		50		Ohms
Insertion Loss			0.5	dB
Attenuation Value		0 to 70		dB
Step Size		10		dB
Step Type		Rotary		
Accuracy Statement	± 0.5 dB or 3% (Whichever is greater)			
Input Power			2	Watts
Input Power, Peak			1	KWatts

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Range	DC to 1	1 to 2.2				GHz
Insertion Loss	0.3	0.5				dB
VSWR	1.2:1	1.4:1				

Electrical Specification Notes:
Specs by Frequency are maximum values

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz PE70A1022](#)



0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz

RF Step Attenuators Technical Data Sheet

PE70A1022

Mechanical Specifications

Size

Length 2.67 in [67.82 mm]
 Width 1.5 in [38.1 mm]
 Weight 0.571 lbs [259 g]
 Body Material and Plating Aluminum, Chem Film

Connectors

Description	Connector 1	Connector 2
Type	BNC Female	BNC Female

Environmental Specifications

Temperature

Operating Range -20 to 85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz PE70A1022](#)



0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz

RF Step Attenuators Technical Data Sheet

PE70A1022



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz PE70A1022](#)



0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz

RF Step Attenuators Technical Data Sheet

PE70A1022

0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female With 10 dB Step Rated to 2 Watts Up to 2.2 GHz PE70A1022](https://www.pasternack.com/70db-step-bnc-female-bnc-female-2-watts-attenuator-pe70a1022-p.aspx)

URL: <https://www.pasternack.com/70db-step-bnc-female-bnc-female-2-watts-attenuator-pe70a1022-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE70A1022 CAD Drawing

0 to 70 dB Rotary Step Attenuator, BNC Female to BNC Female
With 10 dB Step Rated to 2 Watts Up to 2.2 GHz



STANDARD TOLERANCES
 .X ± 0.2
 .XX ± 0.1
 .XXX ± 0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

<p>NOTES:</p> <ol style="list-style-type: none"> 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. 	
<p>DWG TITLE</p> <h2>PE70A1022</h2>	
<p>CAGE CODE</p> <p>53919</p>	<p>CAD FILE</p> <p>121316</p>
<p>SCALE</p> <p>N/A</p>	<p>SIZE</p> <p>A</p>
<p>2233</p>	

PE PASTERNAK®
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com