

30 dB Fixed Attenuator SMA Male to SMA
Female Black Anodized Aluminum Heatsink
Body Rated 5 Watt DC to 18 GHz



PE7623-30

Features

- DC to 18 GHz Frequency Range
- SMA Connectorized Design
- Attenuation 30 dB \pm 1 dB
- Max Power 5 Watts (CW)
- Max VSWR of 1.3:1

Applications

- Instrumentation
- Precision Measurements
- Prototyping and Characterization
- Production Systems

Description

Pasternack carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuator pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Pasternack carries one of the largest in-stock varieties and ships them same day. The 30 dB Fixed Attenuator PE7623-30 is rated to 5 Watts and operates from DC to 18 GHz. The versatile coaxial package uses SMA male to SMA female connectors and is also REACH compliant.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50		Ohms
Nominal Attenuation		30		dB
Attenuation Accuracy		\pm 1		dB
VSWR			1.3:1	
Input Power, CW			5	Watts
Derated linearly to 0.5W @ 125°C				
Input Power, Peak			500	Watts
5 μ Sec PW, 1% duty cycle				

Mechanical Specifications

Size

- Length 1.34 in [34.04 mm]
- Width/Diameter 0.62 in [15.75 mm]
- Height 0.62 in [15.75 mm]
- Weight 0.01 lbs [4.54 g]
- Body Material and Plating Black Anodized Aluminum

Configuration

- Design Fixed, Bidirectional
- Package Style Connectorized

30 dB Fixed Attenuator SMA Male to SMA
Female Black Anodized Aluminum Heatsink
Body Rated 5 Watt DC to 18 GHz



PE7623-30

Connectors

Description	Connector 1	Connector 2
Type	SMA Male	SMA Female
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel	Brass, Nickel

Environmental Specifications

Temperature

Operating Range -55 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data

30 dB Fixed Attenuator SMA Male to SMA Female Black Anodized Aluminum Heatsink Body Rated 5 Watt DC to 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [30 dB Fixed Attenuator SMA Male to SMA Female Black Anodized Aluminum Heatsink Body Rated 5 Watt DC to 18 GHz PE7623-30](#)

URL: <https://www.pasternack.com/30db-fixed-sma-male-sma-female-5-watts-attenuator-pe7623-30-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE7623-30 CAD Drawing

30 dB Fixed Attenuator SMA Male to SMA Female Black Anodized Aluminum Heatsink Body Rated 5 Watt DC to 18 GHz



(PE) PASTERNAK®
an INFINITE® brand

Website: www.Pasternack.com
 Phone: 1.866.727.8376 | 1.949.261.1920

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5
 SCALE NONE
 SHEET 1 OF 1

DESCRIPTION
30 dB FIXED ATTENUATOR, SMA MALE TO SMA FEMALE BLACK ANODIZED ALUMINUM HEATSINK BODY RATED TO 5 WATTS UP TO 18 GHz

REV	ITEM NO.	SIZE	CAGE CODE	DRAWN BY
A	53919	A	HBAKKE	HBAKKE

PE7623-30