

MMCX Plug to SMA Female Bulkhead Cable Using PE-SR405FL Coax





PE3C5157

Configuration

- Connector 1: MMCX Plug
- Connector 2: SMA Female Bulkhead
- Cable Type: PE-SR405FL
- Coax Flex Type: Formable

Features

- Max Frequency 6 GHz
- 69.5% Phase Velocity



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C5157 MMCX plug to SMA female bulkhead cable using PE-SR405FL coax is part of our full line of RF components available for same-day shipping. Pasternack's formable RF cable assemblies provide an alternative to costly pre-formed semi-rigid assemblies since they are hand formable. This Pasternack MMCX to SMA cable assembly has a plug to female gender configuration with 50 ohm formable PE-SR405FL coax. The PE3C5157 MMCX plug to SMA female cable assembly operates to 6 GHz. Our RF cable assembly with SMA bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	
VSWR			1.4:1	
Velocity of Propagation		69.5		%
Capacitance		29 [95.14]		pF/ft [pF/m]
DC Resistance Inner Conductor		65.7 [215.55]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		10.2 [33.46]		Ohms/1000ft [Ohms/Km]

Specifications by Frequency

MMCX Plug to SMA Female Bulkhead Cable Using PE-SR405FL Coax



PE3C5157

Part Number	Length	Description	F1	F2	F3	F4	Units	Weight (lbs)
		Frequency	500	1000	2500	6000	MHz	
PE3C5157	Custom Lengths Available	Insertion Loss (Typ.)	0.15	0.22	0.34	0.6	dB/ft	
			0.5	0.73	1.12	1.97	dB/m	
PE3C5157-6	6 inch	Insertion Loss (Typ.)	0.78	0.81	0.87	1	dB	0.017
PE3C5157-9	9 inch	Insertion Loss (Typ.)	0.82	0.87	0.96	1.15	dB	0.02
PE3C5157-12	12 inch	Insertion Loss (Typ.)	0.85	0.92	1.04	1.3	dB	0.022
PE3C5157-24	24 inch	Insertion Loss (Typ.)	1	1.14	1.38	1.9	dB	0.034
PE3C5157-36	36 inch	Insertion Loss (Typ.)	1.15	1.36	1.72	2.5	dB	0.045

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1 dB
 Loss due to Connector 2: 0.6 dB
 Base Weight: 0.022 pounds
 Additional Weight per Inch: 0.00092 pounds

Mechanical Specifications

Cable Assembly

Weight 0.022 lbs [9.98 g]

Cable

Cable Type PE-SR405FL
 Impedance 50 Ohms
 Inner Conductor Type Solid
 Inner Conductor Material and Plating Copper Clad Steel, Silver
 Dielectric Type PTFE
 Number of Shields 1
 Outer Conductor 1 Material and Plating Copper, Tin
 Repeated Minimum Bend Radius 0.78 in [19.81 mm]

Connectors

Description	Connector 1	Connector 2
Type	MMCX Plug	SMA Female Bulkhead
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold over Nickel
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Gold	Brass, Gold over Nickel

MMCX Plug to SMA Female Bulkhead Cable Using PE-SR405FL Coax



PE3C5157

Environmental Specifications

Compliance Certifications (see product page for current document)


Plotted and Other Data

Notes:

Typical Performance Data

How to Order

Part Number Configuration:



Example: PE3C5157-12 = 12 inches long cable
PE3C5157-100cm = 100 cm long cable

MMCX Plug to SMA Female Bulkhead Cable Using PE-SR405FL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMA Female Bulkhead Cable Using PE-SR405FL Coax PE3C5157](#)

URL: <https://www.pasternack.com/mmcx-plug-to-sma-female-bulkhead-cable-using-pe-sr405fl-pe3c5157-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3C5157 CAD Drawing

MMCX Plug to SMA Female Bulkhead Cable Using PE-SR405FL Coax

