



SMPS Female to Mini SMP Female
Cable Using PE-P047HF Coax

TECHNICAL DATA SHEET


PE3C9958

Configuration

- Connector 1: SMPS Female
- Connector 2: Mini SMP Female
- Cable Type: PE-P047HF
- Coax Flex Type: Flexible

Features

- Max Frequency 40 GHz
- Shielding Effectivity > 90 dB
- 70% Phase Velocity
- Double Shielded
- FEP Jacket



Applications

- General Purpose
- Laboratory Use
- Scientific research
- High-reliability, high-density for aerospace & defense application
- Ground base station & communication systems, avionics, radar systems

Description

Pasternack's PE3C9958 SMPS female to Mini SMP female cable using PE-P047HF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMPS to Mini SMP cable assembly has a female to female gender configuration with 50 ohm flexible PE-P047HF coax. The PE3C9958 SMPS female to Mini SMP female cable assembly operates to 40 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax PE3C9958](#)



SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax

TECHNICAL DATA SHEET

PE3C9958

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		40	GHz
VSWR			1.5:1	
Velocity of Propagation		70		%
RF Shielding	90			dB
Capacitance		29 [95.14]		pF/ft [pF/m]

Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	2500	5000	10000	20000	40000	MHz	
PE3C9958	Custom Lengths Available	Insertion Loss (Typ.)	0.55	0.8	1.17	1.78	2.77	dB/ft	
			1.81	2.63	3.84	5.84	9.09	dB/m	
PE3C9958-6	6 inch	Insertion Loss (Typ.)	0.5	0.72	1.03	1.52	2.28	dB	0.005
PE3C9958-12	12 inch	Insertion Loss (Typ.)	0.78	1.12	1.62	2.41	3.66	dB	0.007
PE3C9958-18	18 inch	Insertion Loss (Typ.)	1.05	1.52	2.2	3.3	5.05	dB	0.009

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1*SQRT(FGHz) dB
Loss due to Connector 2:	0.04*SQRT(FGHz) dB
Base Weight:	0.007 pounds
Additional Weight per Inch:	0.00033 pounds

Mechanical Specifications

Cable Assembly

Weight 0.00811 lbs [3.68 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax PE3C9958](#)



SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax

TECHNICAL DATA SHEET

PE3C9958

Cable

Cable Type	PE-P047HF
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Tape
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP, Blue
Jacket Diameter	0.06 in [1.52 mm]
Repeated Minimum Bend Radius	0.1 in [2.54 mm]

Connectors

Description	Connector 1	Connector 2
Type	SMPS Female Push-on	Mini SMP Female Push-On
Specification		MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Contact Plating Specification	50 µin minimum	
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Outer Conductor Plating Specification	50 µin minimum	
Body Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Body Plating Specification	30 µin minimum	

Environmental Specifications

Temperature

Operating Range -55 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax PE3C9958](#)



SMPS Female to Mini SMP Female
Cable Using PE-P047HF Coax

TECHNICAL DATA SHEET

PE3C9958

How to Order

Part Number Configuration:

PE3C9958

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C9958-12 = 12 inches long cable
PE3C9958-100cm = 100 cm long cable

SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax PE3C9958](#)


URL: <https://www.pasternack.com/smps-female-to-mini-smp-female-cable-using-pe-p047hf-pe3c9958-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C9958 CAD Drawing

SMPS Female to Mini SMP Female Cable Using PE-P047HF Coax

REVISION			
ZONE	REV.	DESCRIPTION	DATE
	A	INITIAL RELEASE	08/31/2023
			CHANGED BY
			BPUCHASKI
			APPROVED BY
			AGANWANI



NOTES:

- 1. CABLE ASSEMBLY LENGTH DETERMINED BY P/N AS ILLUSTRATED:
PE3C9958-XXX (-XXX = LENGTH IN INCHES)
- 2. CABLE ASSEMBLIES SHALL BE TESTED FOR CONTINUITY

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

TOLERANCES:			
.X = ±.2 [5]	FRACTIONS	± 1/32	
.XX = ±.02 [0.5]	ANGLES	± 1°	
.XXX = ±.005 [0.13]	CABLE LENGTH TOLERANCES:		
	<12 [305]	±.1 [5]	/-0
	>12 [305] ≤ 60 [1524]	±.2 [5]	/-0
	>60 [1524] ≤ 120 [3048]	±.4 [102]	/-0
	>120 [3048] ≤ 300 [7620]	±.6 [152]	/-0
	>300 [7620]	±.5%	/-0

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE IN INCHES. TRAILING DIMENSIONS IN [] ARE IN MILLIMETERS.

ALL DIMENSIONS ARE FOR REFERENCE ONLY. DIMENSIONS OF NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION. COLORS MAY VARY.



Website: www.Pasternack.com
Phone: 1.866.727.8376 | 1.949.261.1920

DESCRIPTION

SMPS FEMALE TO MINI SMP FEMALE CABLE USING PE-P047HF COAX

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5	
SCALE	NONE
SHEET	1 OF 1

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	53919	BPUCHASKI	PE3C9958-XXX	A