


SMPM Size 12 D38999 Contact Pin to SMA Female Cable Using PE-P086 Coax with HeatShrink, LF Solder



PE3M0333

Configuration

- Connector 1: Push-on Mini SMP Pin
- Connector 2: SMA Female
- Cable Type: PE-P086
- Coax Flex Type: Flexible



Features

- Max Frequency: 18 GHz
- Can be installed in all D38999 size 12 inserts
- Lot traceability
- High speed RF cable assembly

Applications

- Military and Aerospace
- Avionics
- Industrial Automation

Description

The PE3M0333 from Pasternack is a D38999 contact cable assembly that is built with a size 12 mini SMP pin contact on one end and a SMA female connector on the other. Pasternack MIL-DTL-38999 (also known as D38999 or 38999) coaxial cable assembly products are used in applications requiring high quality such as laboratory RF test and measurement, rugged and designed for defense/military, production environments, general use, etc. This mini SMP to SMA cable assembly is a part of one of the largest selections of same-day ship coaxial cables for RF, microwave, and millimeter wave interconnect solutions. This high frequency D38999 cable assembly operates at a maximum frequency of 18 GHz.

The RF cable has a FEP jacket of 0.163-inch diameter. This PE3M0333 radio frequency cable assembly can withstand temperatures ranging from -65 to 125 degrees C. Our Mini SMP pin to SMA female cable has a maximum VSWR of 1.4:1. This RF cable assembly with a 0.5-inch diameter has copper clad steel as the cable's inner conducting material and PTFE dielectric type.

This mini SMP pin to SMA female cable assembly is built with PE-P086, which is a flexible coax type. The Pasternack PE3M0333 flexible cable assembly has a 50 Ohm impedance and is double shielded. Additional dimensions, specifications, and CAD drawings for this mini SMP to SMA RF cable are available on our downloadable PDF datasheet.

Mini SMP pin to SMA female cable assembly is just one of more than one million in-stock RF products available. Pasternack is where to buy high quality custom RF cable assembly products for rugged and MIL-STD designed military/defense, aerospace, outdoor and harsh environment, microwave and millimeter wave radio transmitter receiver, component inter-connection and more for RF test & measurement labs, telecom, phase stable, phase and delay matching, and other radio frequency applications can be manufactured. Variations of mini SMP and SMA cable assemblies can also be built and will ship on the same day as well, search this website or contact us for assistance. For further information on similar products, our expert technical support and trained sales team can get you the ideal mini SMP to SMA RF cable assembly as per your requirements.

SMPM Size 12 D38999 Contact Pin to SMA Female
Cable Using PE-P086 Coax with HeatShrink, LF Solder



PE3M0333

Referenced Specifications

| | |
|----------------|---|
| IPC J-STD-001 | Requirements for Soldered Electrical and Electronic Assemblies |
| IPC J-STD-006 | Requirements for Electronic Grade Solder Alloys and Fluxed and Non-Fluxed Solid Solders for Electronic Soldering Applications |
| IPC/WHMA-A-620 | Requirements and Acceptance for Cable and Wire Harness Assemblies |
| MIL-DTL-17 | Cables, Radio Frequency, Flexible and Semirigid, General Specification for |
| MIL-PRF-39012 | Connectors, Coaxial, Radio Frequency, General Specification for |
| MIL-STD-348 | Radio Frequency Connector Interfaces for MIL-DTL-3643, MIL-DTL-3650, MIL-DTL-3655, MIL-DTL-25516, MIL-PRF-31031, MIL-PRF-39012, MIL-PRF-49142, MIL-PRF-55339, MIL-DTL-83517 |
| SAE AS22520 | Crimping Tools, Wire Termination, General Specification For |
| SAE AS23053 | Insulation Sleeving, Electrical, Heat Shrinkable, General Specifications For |
| SAE AS5942 | Marking of Electrical Insulating Materials |
| IPC J-STD-001 | Requirements for Soldered Electrical and Electronic Assemblies |

Material Specifications

| Component | Specification |
|---------------|---|
| Cable | PE-P086 in accordance with PE-P086 datasheet |
| Connector 1 | in accordance with MIL-DTL-38999 |
| Connector 2 | in accordance with MIL-STD-348 |
| Heat Shrink 1 | M23053/5-105-0 in accordance with SAE AS23053 |
| Heat Shrink 2 | M23053/5-105-0 in accordance with SAE AS23053 |
| Solder | SAC305 in accordance with J-STD-006 |

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-------------------------|---------|--------------|---------|--------------|
| Frequency Range | DC | | 18 | GHz |
| VSWR | | | 1.4:1 | |
| Velocity of Propagation | | 70 | | % |
| RF Shielding | 110 | | | dB |
| Capacitance | | 29.4 [96.46] | | pF/ft [pF/m] |

Specifications by Frequency

SMPM Size 12 D38999 Contact Pin to SMA Female
Cable Using PE-P086 Coax with HeatShrink, LF Solder



PE3M0333

| Part Number | Length | Description | F1 | F2 | F3 | F4 | F5 | Units | Weight (lbs) |
|-------------|--------------------------|-----------------------|-----------|------|------|------|-------|-------|--------------|
| | | | Frequency | | 1000 | 2000 | 4500 | 9000 | |
| PE3M0333 | Custom Lengths Available | Insertion Loss (Typ.) | 0.19 | 0.28 | 0.43 | 0.63 | 0.951 | dB/ft | |
| | | | 0.63 | 0.91 | 1.41 | 2.08 | 3.13 | dB/m | |
| PE3M0333-6 | 6 inch | Insertion Loss (Typ.) | 0.3 | 0.34 | 0.42 | 0.52 | 0.68 | dB | 0.0265 |
| PE3M0333-12 | 12 inch | Insertion Loss (Typ.) | 0.4 | 0.48 | 0.63 | 0.84 | 1.16 | dB | 0.033 |
| PE3M0333-24 | 24 inch | Insertion Loss (Typ.) | 0.59 | 0.76 | 1.06 | 1.47 | 2.11 | dB | 0.046 |
| PE3M0333-36 | 36 inch | Insertion Loss (Typ.) | 0.78 | 1.04 | 1.49 | 2.1 | 3.06 | dB | 0.059 |
| PE3M0333-48 | 48 inch | Insertion Loss (Typ.) | 0.97 | 1.31 | 1.91 | 2.73 | 4.01 | dB | 0.072 |
| PE3M0333-60 | 60 inch | Insertion Loss (Typ.) | 1.16 | 1.59 | 2.34 | 3.36 | 4.96 | dB | 0.085 |

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1 dB
 Loss due to Connector 2: 0.1 dB
 Base Weight: 0.033 pounds
 Additional Weight per Foot: 0.013 pounds

Electrical Specification Notes:
 Values at 25°C, sea level.

Mechanical Specifications

Cable Assembly

| Description | Minimum | Typical | Maximum | Units |
|------------------------------|---------|---------------|---------|---------|
| Length* | | | 0 [0] | in [mm] |
| Cable Outer Diameter | | 0.163 | | in |
| Weight | | 0.033 [14.97] | | lbs [g] |
| Repeated Minimum Bend Radius | 0.5 | | | in |

Cable Characteristics

| Description | Specification |
|--------------------------------------|----------------------------|
| Cable Type | PE-P086 |
| Impedance | 50 Ohms |
| Inner Conductor Type | Solid |
| Inner Conductor Material and Plating | Copper Clad Steel, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 2 |
| Shield Layer 1 | Silver Plated Copper Tape |
| Shield Layer 2 | Silver Plated Copper Braid |
| Jacket Material | FEP |

SMPM Size 12 D38999 Contact Pin to SMA Female
Cable Using PE-P086 Coax with HeatShrink, LF Solder



PE3M0333

Connector Characteristics

| Description | Connector 1 | Connector 2 |
|--------------------------------------|------------------------|------------------------|
| Type | Mini SMP Pin | SMA Female |
| Specification | MIL-DTL-38999 | MIL-STD-348 |
| Impedance | 50 Ohms | 50 Ohms |
| Configuration | Straight | Straight |
| Connection Method | Push-on | |
| Contact Size | 12 | |
| Mating Cycles | 1,000 | |
| Contact Material and Plating | Beryllium Copper, Gold | Beryllium Copper, Gold |
| Contact Plating Specification | | MIL-G-45204 |
| Dielectric Type | PTFE | PTFE |
| Outer Conductor Material and Plating | Beryllium Copper, Gold | Stainless Steel, Gold |
| Body Material and Plating | Beryllium Copper, Gold | Stainless Steel, Gold |
| Body Plating Specification | | MIL-G-45204 |

Mechanical Specification Notes:

Environmental Specifications

| Description | Specification |
|-----------------------------|-------------------|
| Temperature Operating Range | -65 to +125 deg C |

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:
Values at 25°C, sea level.

SMPM Size 12 D38999 Contact Pin to SMA Female Cable Using PE-P086 Coax with HeatShrink, LF Solder




PE3M0333

How to Order

Part Number Configuration:

PE3M0333 - xx uu



Example: PE3M0333-12 = 12 inches long cable
PE3M0333-100cm = 100 cm long cable

Cable Assembly Length Tolerances:

| Imperial English | | Metric | |
|---------------------|-----------------|---------------------|------------------|
| "L" ≤ 1 ft | +0.5 in / -0 in | "L" ≤ 0.3 m | +12.5 mm / -0 mm |
| 1 ft < "L" ≤ 5 ft | +1 in / -0 in | 0.3 m < "L" ≤ 1.5 m | +25 mm / -0 mm |
| 5 ft < "L" ≤ 10 ft | +2 in / -0 in | 1.5 m < "L" ≤ 3 m | +50 mm / -0 mm |
| 10 ft < "L" ≤ 25 ft | +3 in / -0 in | 3 m < "L" ≤ 7.5 m | +75 mm / -0 mm |
| 25 ft < "L" | +2%"L" / -0%"L" | 7.5 m < "L" | +2%"L" / -0%"L" |

* Cable Length = "L"

SMPM Size 12 D38999 Contact Pin to SMA Female Cable Using PE-P086 Coax with HeatShrink, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPM Size 12 D38999 Contact Pin to SMA Female Cable Using PE-P086 Coax with HeatShrink, LF Solder PE3M0333](https://www.pasternack.com/smpm-size-12-d38999-contact-pin-to-sma-female-cable-using-pe-p086-coax-with-heatshrink-lf-solder-pe3m0333-p.aspx)

URL: <https://www.pasternack.com/smpm-size-12-d38999-contact-pin-to-sma-female-cable-using-pe-p086-coax-with-heatshrink-lf-solder-pe3m0333-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3M0333 CAD Drawing

SMPM Size 12 D38999 Contact Pin to SMA Female Cable Using PE-P086 Coax with HeatShrink, LF Solder

