




MATERIALS	
BODY	BRASS NICKEL PLATED
CONTACT	GOLD PLATED
INSULATOR	PTFE




PASTERNAK ENTERPRISES, INC.
P.O BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451
WEB ADDRESS: www.paternack.com
E-MAIL ADDRESS: sales@paternack.com
COAXIAL & FIBER OPTICS

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.

SIZE A FSCM NO. 53919 CAD FILE 080702 SCALE N/A 127

MATERIALS	
BODY	BRASS NICKEL PLATED
CONTACT	GOLD PLATED
INSULATOR	PTFE



PASTERНАCK ENTERPRISES, INC.

P.O. BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasterнак.com
E-MAIL ADDRESS: sales@pasterнак.com

DES. N FEMALE, CRIMP ATTACHMENT FOR RG58
COAXIAL & FIBER OPTICS

PE4436

DWG TITLE

CONTACT: .068" HEX CRIMP TOOL

FERRULE: .213" HEX CRIMP TOOL

SIZE A

FSCM NO. 53919

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

N

FEMALE

CRIMP

ATTACHMENT

FOR RG58

COAXIAL & FIBER OPTICS

PE4436

ESTABLISHED 1972

PE4436

DES.

Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket

RF Cables Technical Data Sheet

PE-C195

Configuration

- Low Loss Flexible Cable
- 2 Shield(s)

Features

- Low Loss
- Double Shielded
- PE Jacket
- Velocity of Propagation 80%
- Shielding Effectiveness > 90 dB

Applications

- Antenna Feeds
- Communication Systems
- Wireless Systems
- Indoor / Outdoor Uses
- Direct Burial
- Jumper Cable Assemblies

Description

Flexible coaxial cable are ideal for applications where tight bends and continual flexure are required. Pasternack's PE-C195 is a low loss flexible RG58 type coax cable with PE jacket. The double shielding of this low loss cable provides better electrical performance than the standard RG-58 cable including excellent shielding effectiveness of better than 90 dB. This Pasternack cable's PE jacket makes it suitable for indoor/outdoor uses and direct burial applications. PE-C195 RG58 type datasheet specifications and outline drawing for this flexible cable are shown in the PDF below.

Pasternack carries a wide range of cables ready to ship same day to fit your needs. They are available in corrugated, flexible, formable or semi-rigid versions with different constructions of conductor materials, dielectric materials, shielding configurations and jacket materials. Our cables are designed to fit a wide range of performance criteria including attenuation, operating temperature, environmental factor, and power capability.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		5.8	GHz
Cutoff Frequency		41		GHz
Impedance		50		Ohms
Velocity of Propagation		80		%
Shielding Effectiveness	90			dB
Jacket Spark			5,000	Vrms
Nominal Capacitance		25.4 [83.33]		pF/ft [pF/m]
Input Power (Peak)			2.5	KWatts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket PE-C195](#)

Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket

RF Cables Technical Data Sheet

PE-C195

Performance by Frequency Band

Description	F1	F2	F3	F4	F5	Units
Frequency	0.15	0.22	0.45	0.9	1.5	GHz
Attenuation, Max	4.4	5.4	7.8	11.1	14.5	dB/100ft
	14.44	17.72	25.59	36.42	47.57	dB/100m
Attenuation, Typ	4.3	5.2	7.5	10.7	13.4	dB/100ft
	14.11	17.06	24.61	35.1	43.96	dB/100m
Input Power (CW), Max	350	290	200	140	110	Watts
Description	F6	F7	F8	F9	F10	Units
Frequency	1.8	2	2.5	5.8		GHz
Attenuation, Max	16	16.9	19	29.9		dB/100ft
	52.49	55.45	62.34	98.1		dB/100m
Attenuation, Typ	15.3	16.1	18.1	28.2		dB/100ft
	50.2	52.82	59.38	92.52		dB/100m
Input Power (CW), Max	100	90	80	50		Watts

Mechanical Specifications

Diameter	0.195 in [4.95 mm]
Weight	0.021 lbs/ft [0.03 Kg/m]
Min. Bend Radius (Installation)	0.5 in [12.7 mm]
Min. Bend Radius (Repeated)	2 in [50.8 mm]

Construction Specifications

Description	Material and Plating	Diameter
Inner Conductor	Copper, 1 Strands	0.037 in [0.94 mm]
Conductor Type	Solid	
Dielectric	PE (F)	0.11 in [2.79 mm]
First Shield	Aluminum Tape	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket PE-C195](#)

Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket

RF Cables Technical Data Sheet

PE-C195

Second Shield	Tinned Copper Braid	0.139 in [3.53 mm]
Jacket	PE, Black	0.195 in [4.95 mm]

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Installation Range

-70 to +85 deg C

Storage Range

-40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket PE-C195](#)

URL: <https://www.pasternack.com/flexible-0.195-50-ohm-coax-cable-pe-jacket-pe-c195-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE-C195 CAD Drawing

Low Loss Flexible RG58 Type Coax Cable Double Shielded with Black PE Jacket



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE	PE-C195
FSCM NO.	53919

CAD FILE	111716	SCALE	N/A	SIZE	A
					41742

PASTERNACK®	
THE ENGINEER'S RF SOURCE	
Pasternack Enterprises, Inc.	
P.O. Box 16759	Irvine CA 92623
Phone: (949) 261-1920	Fax: (949) 261-7451
Website: www.pasternack.com	E-Mail: sales@pasternack.com