

TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax



RF Cable Assemblies Technical Data Sheet



PE3W09931-36

Configuration

- Connector 1: TNC Male
- Connector 2: TNC Female 4 Hole Flange
- Cable Type: RG188-DS

Features

- Max Frequency 2 GHz
- Double Shielded
- PTFE Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W09931-36 TNC male to TNC female 4 hole flange 36 inch cable using RG188-DS coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to TNC cable assembly has a male to female gender configuration with 50 ohm flexible RG188-DS coax. The PE3W09931-36 TNC male to TNC female cable assembly operates to 2 GHz. Our RF cable assembly with TNC 4 hole flange interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax PE3W09931-36](#)

TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax



RF Cable Assemblies Technical Data Sheet

PE3W09931-36

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2	GHz
VSWR			1.45:1	
Capacitance	32 [104.99]			pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.05	0.1	0.25	0.5	2	GHz
Insertion Loss (Max.)	0.32	0.35	0.41	0.53	1.22	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Length*	36 in [914.4 mm]
Diameter	0.69 in [17.53 mm]

Cable

Cable Type	RG188-DS
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	PTFE, White
Jacket Diameter	0.118 in [3 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax PE3W09931-36](#)

TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax



RF Cable Assemblies Technical Data Sheet

PE3W09931-36

Connectors

Description	Connector 1	Connector 2
Type	TNC Male	TNC Female 4 Hole Flange
Specification	MIL-STD-348A	MIL-STD-348
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold
Contact Plating Specification	30 μ in. minimum	
Dielectric Type	Teflon	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 μ in. minimum	

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax PE3W09931-36](#)

TNC Male to TNC Female 4 Hole Flange Cable
36 Inch Length Using RG188-DS Coax



RF Cable Assemblies Technical Data Sheet

PE3W09931-36

How to Order

Part Number Configuration:

PE3W09931

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W09931-12 = 12 inches long cable
PE3W09931-100cm = 100 cm long cable

TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax PE3W09931-36](#)

URL: <https://www.pasternack.com/tnc-male-tnc-female-rg188-ds-cable-assembly-pe3w09931-36-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3W09931-36 CAD Drawing

TNC Male to TNC Female 4 Hole Flange Cable 36 Inch Length Using RG188-DS Coax

