

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax




PE3W10447

Configuration

- Connector 1: BNC Female Bulkhead
- Connector 2: BNC Female Bulkhead
- Cable Type: RG223
- Coax Flex Type: Flexible

Features

- Max Frequency 2 GHz
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W10447 BNC female bulkhead to BNC female bulkhead cable using RG223 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to BNC cable assembly has a female to female gender configuration with 50 ohm flexible RG223 coax. The PE3W10447 BNC female to BNC female cable assembly operates to 2 GHz. Our RF cable assembly with BNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2	GHz
VSWR			1.4:1	
Velocity of Propagation	66			%
Capacitance	30.8 [101.05]			pF/ft [pF/m]
Operating Voltage (AC)			500	Vrms

Specifications by Frequency

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax



PE3W10447

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	50	100	250	500	2000	MHz	
PE3W10447	Custom Lengths Available	Insertion Loss (Typ.)	0.01	0.02	0.06	0.09	0.191	dB/ft	
			0.04	0.07	0.19	0.3	0.63	dB/m	
PE3W10447-12	12 inch	Insertion Loss (Typ.)	0.22	0.22	0.26	0.29	0.4	dB	0.127
PE3W10447-24	24 inch	Insertion Loss (Typ.)	0.23	0.24	0.32	0.38	0.59	dB	0.159
PE3W10447-36	36 inch	Insertion Loss (Typ.)	0.24	0.26	0.37	0.47	0.78	dB	0.19
PE3W10447-60	60 inch	Insertion Loss (Typ.)	0.26	0.3	0.48	0.65	1.16	dB	0.252
PE3W10447-72	72 inch	Insertion Loss (Typ.)	0.27	0.32	0.54	0.74	1.35	dB	0.283

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1 dB

Loss due to Connector 2: 0.1 dB

Base Weight: 0.127 pounds

Additional Weight per Inch: 0.00259 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter 0.5 in [12.7 mm]
Weight 0.127 lbs [57.61 g]

Cable

Cable Type	RG223
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	PVC, Black
Jacket Diameter	0.209 in [5.31 mm]
Repeated Minimum Bend Radius	1 in [25.4 mm]

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax



PE3W10447

Connectors

Description	Connector 1	Connector 2
Type	BNC Female Bulkhead	BNC Female Bulkhead
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 μ in minimum	30 μ in minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 μ in minimum	100 μ in minimum

Environmental Specifications

Operating Range Temperature -40 to +80 deg C

Compliance Certifications

(see [product page](#) for current document)

Plotted and Other Data

Notes:

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax




PE3W10447

Typical Performance Data

How to Order

Part Number Configuration:



Example: PE3W10447-12 = 12 inches long cable
PE3W10447-100cm = 100 cm long cable

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax PE3W10447](#)

URL: <https://www.pasternack.com/bnc-female-bulkhead-to-bnc-female-bulkhead-cable-using-rg223-pe3w10447-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W10447 CAD Drawing

BNC Female Bulkhead to BNC Female Bulkhead Cable Using RG223 Coax

