



TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax

RF Cable Assemblies Technical Data Sheet


PE3W11000

Configuration

- Connector 1: TNC Male
- Connector 2: SMA Jack Reverse Polarity Bulkhead
- Cable Type: RG58

Features

- 65.9% Phase Velocity
- PVC (NC) Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W11000 TNC male to reverse polarity SMA jack bulkhead cable using RG58 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to reverse polarity SMA cable assembly has a male to jack gender configuration with 50 ohm flexible RG58 coax. Our RF cable assembly with SMA bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		65.9		%
Capacitance		30.8 [101.05]		pF/ft [pF/m]

Mechanical Specifications

Cable Assembly

Weight 0.071 lbs [32.21 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax PE3W11000](#)



TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax

RF Cable Assemblies Technical Data Sheet

PE3W11000

Cable

Cable Type	RG58
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Tin
Dielectric Type	PE
Number of Shields	1
Shield Layer 1	Tinned Copper Braid
Jacket Material	PVC (NC), Black
Jacket Diameter	0.195 in [4.95 mm]
One Time Minimum Bend Radius	0.98 in [24.89 mm]
Repeated Minimum Bend Radius	1.96 in [49.78 mm]

Connectors

Description	Connector 1	Connector 2
Type	TNC Male	SMA Jack Reverse Polarity Bulkhead
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	
Contact Plating Specification	30 µin minimum	
Dielectric Type	PTFE	
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 µin minimum	
Coupling Nut Material and Plating	Brass, Nickel	
Coupling Nut Plating Specification	100 µin minimum	

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax PE3W11000](#)



TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax

RF Cable Assemblies Technical Data Sheet

PE3W11000

How to Order

Part Number Configuration:

PE3W11000

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3W11000-12 = 12 inches long cable
PE3W11000-100cm = 100 cm long cable

TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax PE3W11000](https://www.pasternack.com/tnc-male-to-reverse-polarity-sma-jack-bulkhead-cable-using-rg58-pe3w11000-p.aspx)

URL: <https://www.pasternack.com/tnc-male-to-reverse-polarity-sma-jack-bulkhead-cable-using-rg58-pe3w11000-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax

TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE IN INCHES DIMENSIONS IN [] ARE MILLIMETERS	 		INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5		1 OF 1
	TOLERANCES: $X \pm .2$ [5] FRACTIONS $XX \pm .02$ [.5] +1/32 $XXX \pm .005$ [.13] ANGLES $\pm 1^\circ$		SCALE NONE	SHEET 1	
DESCRIPTION					
TNC Male to Reverse Polarity SMA Jack Bulkhead Cable Using RG58 Coax					
Website: www.Pasternack.com					
Phone: 1.866.727.8376 1.949.261.1920					
SIZE	CAGE CODE	DRAWN BY	ITEM NO.		
A	53919	BPUCHASKI		PE3W11000	
ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE.					

- NOTES:
1. CABLE ASSEMBLY LENGTH LABEL PLACEMENT: 36 INCHES OR LESS , ONE LABEL APPROXIMATELY CENTERED , LONGER THAN 36 INCHES, TWO LABELS APPROXIMATELY 6 INCHES FROM EACH CONNECTOR.
 2. CABLE ASSEMBLIES SHALL BE TESTED FOR CONTINUITY
- THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN WHOLE OR WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.