

NEX10 Male Right Angle to N Male Right Angle Low PIM Cable Using 1/4 inch Superflexible Coax




PE3W14576

Configuration

- Connector 1: NEX10 Male Right Angle
- Connector 2: N Male Right Angle
- Cable Type: 1/4" Superflexible
- Coax Flex Type: Corrugated

Features

- Max Frequency 6 GHz
- Low PIM: -160 dBc Max
- Shielding Effectivity > 120 dB
- 82% Phase Velocity
- PE Jacket



Applications

- General Purpose
- Laboratory Use
- Low PIM Applications

Description

Pasternack's PE3W14576 NEX10 male right angle to type N male right angle cable using 1/4 inch superflexible coax is part of our full line of RF components available for same-day shipping. Pasternack's corrugated RF cable assemblies are ideal for applications where durability and high power are needed. This Pasternack NEX10 to type N cable assembly has a male to male gender configuration with 50 ohm corrugated 1/4" superflexible coax. The PE3W14576 NEX10 male to type N male cable assembly operates to 6 GHz. Our low PIM design also offers excellent passive intermodulation performance with PIM levels better than -160 dBc. The right angle NEX10 and right angle type N interfaces on the 1/4" superflexible cable allow for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.4:1	
Velocity of Propagation		82		%
RF Shielding	120			dB
Passive Intermodulation IM3 (2x43dBm Tones) at 850 MHz or 1900 MHz			-160	dBc
Capacitance		24.4 [80.05]		pF/ft [pF/m]
Inductance		0.059 [0.19]		uH/ft [uH/m]
DC Resistance Inner Conductor		3.2 [10.5]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		2.53 [8.3]		Ohms/1000ft [Ohms/Km]

NEX10 Male Right Angle to N Male Right Angle
Low PIM Cable Using 1/4 inch Superflexible Coax



PE3W14576

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Dielectric Withstanding Voltage (AC)			750	Vrms
Jacket Spark			2,000	Vrms

Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	100	250	500	1000	3000	MHz	
PE3W14576	Custom Lengths Available	Insertion Loss (Typ.)	0.016	0.027	0.039	0.058	0.107	dB/ft	
			0.06	0.09	0.13	0.2	0.36	dB/m	
PE3W14576-12	12 inch	Insertion Loss (Typ.)	0.42	0.43	0.44	0.46	0.51	dB	0.182
PE3W14576-24	24 inch	Insertion Loss (Typ.)	0.44	0.46	0.48	0.52	0.62	dB	0.224
PE3W14576-36	36 inch	Insertion Loss (Typ.)	0.45	0.49	0.52	0.58	0.73	dB	0.266
PE3W14576-48	48 inch	Insertion Loss (Typ.)	0.47	0.51	0.56	0.64	0.83	dB	0.308
PE3W14576-60	60 inch	Insertion Loss (Typ.)	0.48	0.54	0.6	0.69	0.94	dB	0.35

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.2 dB
Loss due to Connector 2:	0.2 dB
Base Weight:	0.182 pounds
Additional Weight per Inch:	0.0035 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.182 lbs [82.55 g]

Cable

Cable Type	1/4" Superflexible
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	PE (F)
Number of Shields	1
Shield Layer 1	Helically Corrugated Copper Tube
Jacket Material	PE, Black
Jacket Diameter	0.303 in [7.7 mm]
One Time Minimum Bend Radius	0.5 in [12.7 mm]
Repeated Minimum Bend Radius	1 in [25.4 mm]
Typical Flex Cycles	20
Tensile Strength	79 lbs [35.83 Kg]

NEX10 Male Right Angle to N Male Right Angle
Low PIM Cable Using 1/4 inch Superflexible Coax



PE3W14576

Connectors

Description	Connector 1	Connector 2
Type	NEX10 Male Right Angle	N Male Right Angle
Impedance	50 Ohms	50 Ohms
Configuration	Right Angle	Right Angle
Contact Material and Plating	Brass, Silver	Brass, Silver
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal

Environmental Specifications

Operating Range Temperature -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


NEX10 Male Right Angle to N Male Right Angle
Low PIM Cable Using 1/4 inch Superflexible Coax



PE3W14576

Typical Performance Data

How to Order



Example: PE3W14576-12 = 12 inches long cable
 PE3W14576-100cm = 100 cm long cable

NEX10 Male Right Angle to N Male Right Angle Low PIM Cable Using 1/4 inch Superflexible Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [NEX10 Male Right Angle to N Male Right Angle Low PIM Cable Using 1/4 inch Superflexible Coax PE3W14576](#)

URL: <https://www.pasternack.com/nex10-male-right-angle-to-n-male-low-pim-cable-using-1-4-inch-superflexible-pe3w14576-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W14576 CAD Drawing

NEX10 Male Right Angle to N Male Right Angle Low PIM Cable Using 1/4 inch Superflexible Coax

