

## N Male to UHF Male Cable Using RG393 Coax




### PE3W19015

#### Configuration

- Connector 1: N Male
- Connector 2: UHF Male
- Cable Type: RG393
- Coax Flex Type: Flexible

#### Features

- Max Frequency 300 MHz
- 69.5% Phase Velocity
- Double Shielded
- FEP Jacket



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE3W19015 type N male to UHF male cable using RG393 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to UHF cable assembly has a male to male gender configuration with 50 ohm flexible RG393 coax. The PE3W19015 type N male to UHF male cable assembly operates to 300 MHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		300	GHz
VSWR			1.4:1	
Velocity of Propagation		69.5		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

#### Specifications by Frequency

## N Male to UHF Male Cable Using RG393 Coax



### PE3W19015

Part Number	Length	Description	F1	F2	F3	F4	Units	Weight (lbs)
			Frequency	50	100	250	300	
PE3W19015	Custom Lengths Available	Insertion Loss (Typ.)	0.01	0.02	0.03	0.03	dB/ft	
			0.05	0.07	0.1	0.11	dB/m	
PE3W19015-12	12 inch	Insertion Loss (Typ.)	0.22	0.23	0.23	0.24	dB	0.306
PE3W19015-24	24 inch	Insertion Loss (Typ.)	0.23	0.25	0.26	0.27	dB	0.464
PE3W19015-36	36 inch	Insertion Loss (Typ.)	0.24	0.27	0.29	0.3	dB	0.622
PE3W19015-60	60 inch	Insertion Loss (Typ.)	0.27	0.31	0.35	0.37	dB	0.937
PE3W19015-72	72 inch	Insertion Loss (Typ.)	0.28	0.33	0.38	0.4	dB	1.094

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.306 pounds
Additional Weight per Inch:	0.01313 pounds

### Mechanical Specifications

#### Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.306 lbs [138.8 g]

#### Cable

Cable Type	RG393
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.39 in [9.91 mm]
Repeated Minimum Bend Radius	3.9 in [99.06 mm]

## N Male to UHF Male Cable Using RG393 Coax



### PE3W19015

#### Connectors

Description	Connector 1	Connector 2
Type	N Male	UHF Male
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 µin minimum	
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 µin minimum	
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100 µin minimum	

#### Environmental Specifications

Operating Range Temperature -55 to +165 deg C

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

## N Male to UHF Male Cable Using RG393 Coax



### PE3W19015

#### Typical Performance Data

#### How to Order

Part Number Configuration:

**PE3W19015**

- **xx**

**uu**

Unit of Measure:

cm = Centimeters

<blank> = Inches

Length

Base Number

Example: PE3W19015-12 = 12 inches long cable  
PE3W19015-100cm = 100 cm long cable

N Male to UHF Male Cable Using RG393 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to UHF Male Cable Using RG393 Coax PE3W19015](#)

URL: <https://www.pasternack.com/n-male-to-uhf-male-cable-using-rg393-pe3w19015-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

# PE3W19015 CAD Drawing

N Male to UHF Male Cable Using RG393 Coax

