

1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB, 8 Bits, 0.5 dB Step Size, Field Replaceable SMA

PE70A5018



Features

- Absorptive Programmable Voltage Controlled Attenuator
- 1 GHz to 20 GHz
- Attenuation Range 0 to 127.5 dB typ
- 0.5 dB Step Size
- 8 Bits
- Digital TTL Logic Control
- Insertion Loss 11 dB
- Attenuation Flatness +/- 4 dB typ
- Input P0.1 dB Compression Power +25 dBm typ
- Input IP3 44 dBm typ
- Max RF Input Power (CW) +27 dBm
- Switching Speed 200 nsec typ
- Dual DC Supply +5V/-5V @ 250mA/130mA
- 50 Ohm Design
- Field Replaceable SMA Female RF Connectors
- Micro-D15 Female connector for DC Bias and Command Control
- Operational Temperature Range -40°C to +85°C
- Rugged and Compact Aluminum Gold Plated Package Design
- Guaranteed Environmental Test Conditions Altitude, Vibration, Humidity, Shock
- Single Positive Control Line Per Bit

Applications

- Test & Measurement
- Military and Commercial Communications
- Military Electronic Systems
- Research & Development

Description

The PE70A5017 is an Absorptive 8 Bit Digitally Controlled Programmable Attenuator that operates across a broadband frequency from 1 GHz to 20 GHz. The 50 Ohm design supports TTL control logic and has an attenuation range that covers 0 to 127.5 dB in 0.5 dB steps. Attenuation steps are 0.5, 1, 2, 4, 8, 16, 32, and 64 dB. Insertion loss is 11 dB typical with a maximum RF input power of +27 dBm. Additional typical performance includes attenuation flatness of +/- 4 dB, Input P0.1dB compression power of +25 dBm, input IP3 of 44 dBm, and switching speed of 200 nsec. The unit requires a dual bias supply of +5V/-5V with DC current of 250mA/130 mA max. The low profile pin package is aluminum with Gold plating and supports field replaceable SMA RF connectors and a Micro-D15 female connector for DC Bias and Command Control functions. The module has an operational temperature range from -40°C to +85°C and is guaranteed to meet a series of environmental test conditions for Altitude, Vibration, Humidity, and Shock.

Electrical Specifications (Values at +25°C, sea level)

Description	Min	Typ	Max	Unit
Frequency Range	1		20	GHz
Impedance		50		Ohms
Attenuation Range		127.5		
Insertion Loss		11	15	dB
VSWR		1.9:1	2.3:1	
Input at 0.1 dB Compression Point		+25		dB
Input IP3			+44	dBm
Survial Power Average -40 to +85 deg C				
DC Voltage		+5		Vdc
TTL Low for Thru Path		0 to 0.8V		Vdc
TTL High for Attenuation		2-5V		Vdc
Step Size		0.5		dB
Switching Speed		200		ns

1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA



PE70A5018

Electrical Specifications (Values at +25°C, sea level)

Description	Min	Typ	Max	Unit
RF Input Power			27	dBm
Control Bits		8		Bits
Bias Current			250/130	mA
IL Temperature Coefficient		0.01		dB/deg C

*Referenced to Insertion Loss

Absolute Maximum Rating

Parameter	Rating
Biasing	+5V±10%/-5V±10%
RF Input power	+30dBm

Mechanical Specifications

Size

Length	1.5 in [38.1 mm]
Width	0.37 in [9.4 mm]
Height	1.42 in [36.07 mm]
Weight	0.05 lbs [22.68 g]
Connector 1	Field Replaceable SMA Female
Connector 2	Field Replaceable SMA Female

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-50 to +105 deg C
Humidity	100% RH at 35°C, 95% RH at 40°C
Shock	20G for 11 msec half sine wave, 3 axis both directions
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Altitude	30,000 Feet

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25 °C, sea level


1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA




PE70A5018

Typical Performance Data


Insertion Loss @+25°C




Input VSWR @+25°C



Output VSWR @+25°C



Insertion Loss @-40°C




1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA


PE70A5018




Input VSWR @-40°C




Output VSWR @-40°C



Insertion Loss @+85°C



Input VSWR @+85°C




1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA


PE70A5018




Output VSWR @+85°C




Attenuation vs. Frequency



VSWR vs. Attenuation(S11)



VSWR vs. Attenuation(S22)




1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA




PE70A5018


Attenuation Range Linearity




Attenuation Step Error Per Bit (dB)



Accumulated Attenuation Error(dB)



Relative Phase Shift




1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA


PE70A5018




IIP3



Speed



Speed



1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB,
8 Bits, 0.5 dB Step Size, Field Replaceable SMA



PE70A5018

1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB, 8 Bits, 0.5 dB Step Size, Field Replaceable SMA from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB, 8 Bits, 0.5 dB Step Size, Field Replaceable SMA PE70A5018](https://www.pasternack.com/bench-top-127.5db-ttl-controlled-sma-female-sma-female-25-dbm-attenuator-pe70a5018-p.aspx)

URL: <https://www.pasternack.com/bench-top-127.5db-ttl-controlled-sma-female-sma-female-25-dbm-attenuator-pe70a5018-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

1 GHz to 20 GHz Digital Control Attenuator, 127.5 dB, 8 Bits, 0.5 dB Step Size, Field Replaceable SMA

