



3dB RF fixed attenuator 10W, DC to 18GHz, TNC male to female

RF Fixed Attenuators Technical Data Sheet

PE7606-3

Features

- Bidirectional
- DC to 18 GHz Range
- Attenuation 3 +/- 1.0 dB

- 10 Watts Average Input Power
- VSWR <1.40:1

Applications

- Precision Measurements
- Production Systems
- Instrumentation
- Prototyping and Characterization

Description

Pasternack carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuators pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Pasternack carries one of the largest in-stock varieties and ships them same day. The 3 dB Fixed Attenuators PE7605-3 is rated to 10 Watts and operates from DC to 18 GHz. The versatile coaxial package uses TNC male to TNC female connectors and is also REACH and RoHS compliant.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50		Ohms
Nominal Attenuation		3		dB
VSWR			1.4:1	
Input Power, CW			10	Watts
Input Power, Peak			1	kWatts
	5μs pulse w/ 0.4% duty cycle			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3dB RF fixed attenuator 10W, DC to 18GHz, TNC male to female PE7606-3](#)



3dB RF fixed attenuator 10W, DC to 18GHz, TNC male to female

RF Fixed Attenuators Technical Data Sheet

PE7606-3

Mechanical Specifications

Size

Length	3.03149 in [77 mm]
Width/Diameter	1.49606 in [38 mm]
Height	1.49606 in [38 mm]
Weight	0.155 lbs [70.31 g]
Body Material and Plating	Black Anodized Aluminum

Configuration

Design	Fixed, Bidirectional
--------	----------------------

Connectors

Description	Connector 1	Connector 2
Type	TNC Male	TNC Female
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel	Brass, Nickel

Environmental Specifications

Temperature

Operating Range	+125 to -55 deg C
-----------------	-------------------

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

3dB RF fixed attenuator 10W, DC to 18GHz, TNC male to female from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3dB RF fixed attenuator 10W, DC to 18GHz, TNC male to female PE7606-3](#)

URL:

PE7606-3 CAD Drawing

3dB RF fixed attenuator 10W, DC to 18GHz, TNC male to female

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	11/27/2023	DMAY	SPONG



PASTERNACK an INFINIT [®] brand		 	
UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS IN INCHES DIMENSIONS IN [] ARE MILLIMETERS TOLERANCES:		INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 SHEET	
$Y = \pm .02 [5]$ $XX = \pm .02 [0.5]$ $XXX = \pm .005 [0.13]$	FRACTIONS: $\pm 1/32$ ANGLES $\pm 1^\circ$	SCALE NONE	1 OF 1
CABLE LENGTH TOLERANCES: ± 12 [305] ± 60 [1524] $\pm 1 + (25) / - 0$ ± 12 [305] ± 60 [1524] ± 2 [51] ± 0 >60 [1524] ± 300 [7620] ± 4 [102] ± 0 >120 [3484] ± 300 [7620] ± 6 [152] ± 0		DESCRIPTION Website: www.Pasternack.com Phone: 1.866.727.8376 1.949.261.1920	
3dB RF FIXED ATTENUATOR 10W, DC TO 18GHz, TNC MALE TO FEMALE		ITEM NO. PE7606-3	
ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE UNLESS INDIVIDUALLY SPECIFIED CABLE LENGTHS VARY IN SIZE AND LOCATION COLOR MAY VARY			
SIZE A	CAGE CODE 53919	DRAWN BY DMAY	REV A

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO US LAW PROHIBITED.