



5900- 7125 MHz, 3 dBi, Stamped Metal AP/ Router Embedded Antenna-50 Pack

Antennas Technical Data Sheet

PESMA1016-50PK

Features

- High Efficiency
- Isotropic radiation patterns
- Linear polarization
- Ultra-Compact design
- Low loss material

- Extended operating temperatures
- Case mounting or on board mount
- Frequency stabilization
- IPEX connector - 80mm cable
- 50-pack for easy buy

Applications

- IoT, M2M, Telemetry, Radar systems
- Wireless Remote Control
- Personal Area Networks (PAN)
- Industrial/Commercial Equipment
- 5 GHz - Wi-Fi/ISM, Wi-Fi 6, 6E, 7 application

- IEEE 802.11 a/n/ac/ax embedded application
- Remote Technology / Monitoring
- Consumer Tracking
- Smart Home / Wearables / Devices
- Agriculture, healthcare, digital signage

Description

Linear polarized antenna PESMA1016-50PK from Pasternack is part of our extensive in-stock omni directional antennas that ship the same day from our ISO 9001:2015 certified facility. The stamped metal antenna has a maximum frequency of 7125 MHz and a minimum frequency of 5900 MHz. This 50-pack stamped metal antenna has a maximum input VSWR of 2:1.

This stamped metal antenna has an overall length of 0.52 inches and a width of 0.36 inches. Pasternack's PESMA1016-50PK is a single band antenna operating from 5900 to 7125 MHz with a 3 dBi gain. Our high-quality 50-pack omni directional antenna has an impedance of 50 Ohms.

Pasternack's experts are on hand to assist you with any inquiries. Order this PESMA1016-50PK 50-pack stamped metal antenna 7 days a week, 24 hours a day, using our on-line ordering system with no MOQs (minimum order quantity) and same-day shipping. Our knowledgeable sales team and ability in the global availability market allow us to lead the industry in supplying RF products like these omni directional antennas.

Configuration

Design
Band Type
Radiation Pattern
Polarization

Stamped Metal
Single
Omni Directional
Linear

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	5,900		7,125	MHz
Input VSWR			2:1	
Impedance		50		Ohms
Gain		3		dBi
Input Power			1	Watt

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [5900- 7125 MHz, 3 dBi, Stamped Metal AP/Router Embedded Antenna-50 Pack PESMA1016-50PK](#)



5900- 7125 MHz, 3 dBi, Stamped Metal AP/ Router Embedded Antenna-50 Pack

Antennas Technical Data Sheet

PESMA1016-50PK

Mechanical Specifications

Size

Overall Length
Width
Height

0.52 in [13.21 mm]
0.36 in [9.14 mm]
0.07 in [1.78 mm]

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

5900- 7125 MHz, 3 dBi, Stamped Metal AP/Router Embedded Antenna-50 Pack from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [5900- 7125 MHz, 3 dBi, Stamped Metal AP/Router Embedded Antenna-50 Pack PESMA1016-50PK](#)

URL: <https://www.pasternack.com/3-stamped-metal-antenna-5900-7125-mhz-4694r-br-connector-pesma1016-50pk-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PESMA1016-50PK CAD Drawing

5900- 7125 MHz, 3 dBi, Stamped Metal AP/Router Embedded Antenna-50 Pack

